Jacobsen®

Product Information Declaration

Tredsafe Inserts Subtle Colours Range

Range Description

This Jacobsen Product Information Declaration (PID)
applies to the accessories range sold by Jacobsen as **Tredsafe Inserts Subtle Colours**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✓ Exterior
✓ High Traffic	✓ Low Traffic	✓ Exposed Sunlight	✓ Wet Areas[1]
✗ ~~Antistatic Environment~~	✓ Clean Room	✓ Over Existing Floor	✓ With Wheels
✗ ~~Under Floor Heating~~	✓ Splash Zones[2]	✓ Commercial Food Prep Areas	✗ ~~Wet Areas[2]~~
✗ ~~Entrance~~			

1. Bathrooms with showers
2. Bathrooms without showers, laundries, kitchens, dining rooms adjacent to sanitary appliances with the right adhesive, and E3 Alternative installation instructions

B
Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	-
Residential	-
Commercial	5 Years
Industrial	-

C
Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	CRF 10.3 kW/m2 (ISO 9239.1:2010)
C3.4 (b) Floor	-

D
Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	SRV 47 (AS 4586:2013) - R11
Suitable for food prep	-

E
Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F
Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	To be tested
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	-

G
Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H
Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

X
Warnings and Bans

Building Act 2004	Product Performance
Section 26	True

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code

V:171126

Product Information Declaration
Tredsafe Inserts Subtle Colours Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tredsafe Inserts Subtle Colours** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration
Tredsafe Inserts Subtle Colours Range

Identifiers

This JPID covers all colours from Tredsafe Inserts Subtle Colours including:

Burgundy 13 mm 12042
Rich Brown 63 mm TS-ISUB-10963
Light Grey 63 mm TS-ISUB-10863
Putty 63 mm TS-ISUB-11063
Neutral Black 63 mm TS-ISUB-10663
Mid Grey 63 mm TS-ISUB-11363
Jade Green 63 mm TS-ISUB-11463
Charcoal Grey v mm TS-ISUB-10763
Burgundy 63 mm TS-ISUB-11263
Royal Blue 63 mm TS-ISUB-11163
Royal Blue 13 mm 12041
Putty 13 mm 12040
Rich Brown 13 mm 12039
Light Grey 13 mm 12038
Neutral Black 53 mm 12091
Light Grey 37 mm 12060
Charcoal Grey 37 mm 12059
Neutral Black 37 mm 12058
Charcoal Grey 13 mm 12037
Neutral Black 13 mm 12036
Burgundy 53 mm 12097
Royal Blue 53 mm 12096
Putty 53 mm 12095
Jade Green 43 mm 12082
Mid Grey 43 mm 12081
Burgundy 43 mm 12080
Royal Blue 43 mm 12079
Putty 43 mm 12078
Rich Brown 53 mm 12094
Light Grey 53 mm 12093
Charcoal Grey 53 mm 12092
Jade Green 53 mm 12099
Charcoal Grey 25mm 12049
Rich Brown 43 mm 12077
Light Grey 43 mm 12076
Mid Grey 53 mm 12098
Jade Green 37 mm 12066
Mid Grey 37 mm 12065
Burgundy 37 mm 12064
Jade Green 13 mm 12044
Mid Grey 13 mm 12043
Charcoal Grey 43 mm 12075
Neutral Black 43 mm 12074
Royal Blue 37 mm 12063
Putty 37 mm 12062
Rich Brown 37 mm 12061
Royal Blue 25 mm TS Insert Royal Blue 25mm
Putty 25 mm TS insert putty 25mm
Jade Green 25 mm TS insert Jade Green 25mm
Mid Grey 25 mm 19203
Burgundy 25 mm TS insert Burgundy 25mm

Sustainability

Rating System	Rating	Product Performance
Green Star Buildings NZ	Responsible Product Value	Calculate RPV here
	Exposure to Toxins	Tests available upon request
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	-
	Credit 21	-
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	-
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	-
Environmental Product Declaration (EPD)		-
Embodied Carbon Emission Data		To be tested

Environmental Credentials

Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328

Tredsafe

Product Manufacturer: **Tredsafe**
Country of Origin: New Zealand