

Product Information Declaration

Tredsafe Inserts Subtle Colours Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as Tredsafe Inserts Subtle Colours

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✓ Exterior
✓ High Traffic	✓ Low Traffic	✓ Exposed Sunlight	✓ Wet Areas
✗ Antistatic Environment	✓ Clean Room	✓ With Wheels	✓ Ramp/Entry
✓ Commercial Food Prep Areas	✗ Under Floor Heating	✓ Over Existing Floor	✓ Splash Zones

B
Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	-
Residential	-
Commercial	5 Years
Industrial	-

C
Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	CRF 10.3 kW/m2 (ISO 9239.1:2010)
C3.4 (b) Floor	-

D
Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	SRV 47 (AS 4586:2013) - R11
Suitable for food prep	-

E
Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F
Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	To be tested
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	-

G
Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H
Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

X
Warnings and Bans

Building Act 2004	Product Performance
Section 26	True

Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](#) or by this QR code



Product Information Declaration

Tredsafe Inserts Subtle Colours Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tredsafe Inserts Subtle Colours** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration

Tredsafe Inserts Subtle Colours Range

Identifiers

This JPID covers all colours from Tredsafe Inserts Subtle Colours including:

Burgundy 13 mm 12042	Charcoal Grey 25mm 12049
Royal Blue 13 mm 12041	Rich Brown 43 mm 12077
Putty 13 mm 12040	Light Grey 43 mm 12076
Rich Brown 13 mm 12039	Mid Grey 53 mm 12098
Light Grey 13 mm 12038	Jade Green 37 mm 12066
Neutral Black 53 mm 12091	Mid Grey 37 mm 12065
Light Grey 37 mm 12060	Burgundy 37 mm 12064
Charcoal Grey 37 mm 12059	Jade Green 13 mm 12044
Neutral Black 37 mm 12058	Mid Grey 13 mm 12043
Charcoal Grey 13 mm 12037	Charcoal Grey 43 mm 12075
Neutral Black 13 mm 12036	Neutral Black 43 mm 12074
Burgundy 53 mm 12097	Royal Blue 37 mm 12063
Royal Blue 53 mm 12096	Putty 37 mm 12062
Putty 53 mm 12095	Rich Brown 37 mm 12061
Jade Green 43 mm 12082	Royal Blue 25 mm TS Insert Royal Blue 25mm
Mid Grey 43 mm 12081	Putty 25 mm TS insert putty 25mm
Burgundy 43 mm 12080	Jade Green 25 mm TS insert Jade Green 25mm
Royal Blue 43 mm 12079	Mid Grey 25 mm 19203
Putty 43 mm 12078	Burgundy 25 mm TS insert Burgundy 25mm
Rich Brown 53 mm 12094	
Light Grey 53 mm 12093	
Charcoal Grey 53 mm 12092	
Jade Green 53 mm 12099	

Sustainability

Rating System	Rating	Product Performance
Green Star Buildings NZ	Responsible Product Value	Calculate RPV here
	Exposure to Toxins	Tests available upon request
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	-
	Credit 21	-
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	-
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	-
Environmental Product Declaration (EPD)		-
Embodied Carbon Emission Data		To be tested

Environmental Credentials

Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328



Product Manufacturer: Tredsafe
Country of Origin: New Zealand