

Product Information Declaration

Tredsafe Diamondtred Zebron Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as Tredsafe Diamondtred Zebron

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✓ Exterior
✓ High Traffic	✓ Low Traffic	✓ Exposed Sunlight	✓ Wet Areas
✗ Antistatic Environment	✓ Clean Room	✓ With Wheels	✓ Ramp/Entry
✓ Commercial Food Prep Areas	✗ Under Floor Heating	✓ Over Existing Floor	✓ Splash Zones

B
Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	-
Residential	-
Commercial	5 Years
Industrial	-

C
Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	CRF 10.3 kW/m2 (ISO 9239.1:2010)
C3.4 (b) Floor	-

D
Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	SRV 47 (AS 4586:2013) - R11
Suitable for food prep	-

E
Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F
Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	To be tested
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	-

G
Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H
Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

X
Warnings and Bans

Building Act 2004	Product Performance
Section 26	True

Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](#) or by this QR code



Product Information Declaration

Tredsafe Diamondtred Zebron Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tredsafe Diamondtred Zebron** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration

Tredsafe Diamondtred Zebron Range

Identifiers

This JPID covers all colours from Tredsafe Diamondtred Zebron including:

Safety Green Zebron 37 mm 12136	Safety Red Zebron 43 mm 12168
Tredsafe Blue Zebron 63 mm 40552	Safety Green Zebron 43 mm 12167
Tredsafe Blue Zebron 53mm 40551	Safety Orange Zebron 43 mm 12166
Tredsafe Blue Zebron 43 mm 40553	Signal Yellow Zebron 37 mm 12148
Tredsafe Blue Zebron 37 mm 40554	Jade Green Zebron 37 mm 12147
Tredsafe Blue Zebron 13 mm 40555	Putty Zebron 53 mm 12189
Safety Pink Zebron 53mm 40545	Rich Brown Zebron 53 mm 12188
Safety Pink Zebron 63 mm 40544	Light Grey Zebron 53 mm 12187
Safety Pink Zebron 43 mm 40543	Safety Grey Zebron 53 mm 12186
Safety Pink Zebron 37 mm 40542	Neutral Black Zebron 53 mm 12185
Safety Pink Zebron 13 mm 40541	Mid Grey Zebron 37 mm 12146
Safety Khaki Zebron 53 mm 40546	Burgundy Zebron 37 mm 12145
Safety Khaki Zebron 63 mm 40550	Royal Blue Zebron 37 mm 12144
Safety Khaki Zebron 43 mm 40547	Safety Blue Zebron 53 mm 12184
Safety Khaki Zebron 37 mm 40548	Putty Zebron 37 mm 12143
Safety Khaki Zebron 13 mm 40549	Rich Brown Zebron 37 mm 12142
Safety Orange Zebron 37 mm 12135	Signal Yellow Zebron 25 mm TS Insert
Light Grey Zebron 37 mm 12141	Signal Yellow Zebron 25mm
Charcoal Grey Zebron 37 mm 12140	Safety White Zebron 25 mm TS Insert
Neutral Black Zebron 37 mm 12139	Safety White Zebron 25mm
Safety Blue Zebron 37 mm 12138	Safety Red Zebron 25 mm TS Insert
Safety Red Zebron 37 mm 12137	Safety Red Zebron 25mm
Lumitred 43 mm 12084	Safety Orange Zebron 25 mm TS Insert
Lumitred 37 mm 12068	Safety Orange Zebron 25mm
Safety White Zebron 37 mm 12134	Safety Green Zebron 25 mm TS Insert
Safety Red Zebron 53 mm 12183	Safety Green Zebron 25mm
Safety Green Zebron 53 mm 12182	Safety Blue Zebron 25 mm TS Insert
Safety White Zebron 53 mm 12180	Safety Blue Zebron 25mm
Signal Yellow Zebron 43 mm 12179	Royal Blue Zebron 25 mm TS Insert
Jade Green Zebron 43mm 12178	Royal Blue Zebron 25mm
Mid Grey Zebron 43 mm 12177	Putty Zebron 25 mm TS insert zebron
Burgundy Zebron 43 mm 12176	25mm
Royal Blue Zebron 43 mm 12175	Neutral Black Zebron 25 mm TS insert
Putty Zebron 43 mm 12174	neutral black zebron 25mm
Rich Brown Zebron 43 mm 12173	Mid Grey Zebron 25 mm TS insert mid
Lumitred 53 mm 12101	Grey 25mm Zebron
Signal Yellow Zebron 53 mm 12194	Charcoal Grey Zebron 25 mm TS insert
Jade Green Zebron 53 mm 12193	Charcoal Grey Zebron 25mm
Burgundy Zebron 53 mm 12191	Light Grey Zebron 25 mm TS insert
Royal Blue Zebron 53 mm 12190	Light Grey 25mm Zebron
Neutral Black Zebron 43 mm 12170	Jade Green Zebron 25 mm TS insert
Light Grey Zebron 43 mm 12172	Jade Green 25mm Zebron
Charcoal Grey Zebron 43 mm 12171	Safety White Zebron 43 mm TS insert
Lumitred 13 mm 12046	Safety White Zebron 43mm
Safety Blue Zebron 43 mm 12169	

Sustainability

Rating System	Rating	Product Performance
Green Star Buildings NZ	Responsible Product Value	Calculate RPV here
	Exposure to Toxins	Tests available upon request
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	-
	Credit 21	-
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	-
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	-
Environmental Product Declaration (EPD)		-
Embodied Carbon Emission Data		To be tested

Environmental Credentials

Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328



Product Manufacturer: Tredsafe
Country of Origin: New Zealand