# **Product Information Declaration**

# **Tredsafe DT031 Range**

# **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as Tredsafe DT031

## **Identifiers**

See individual sku codes under identifiers

# **Scope and Limitations of Intended Use**

×	Residential
×	High Traffic

Antistatic Environment
 Gommercial Food Prep Areas

X Commercial
X Low Traffic

X Clean Room

X Under Floor Heating

**K** Interior

X Exposed Sunlight

X With Wheels

Over Existing Floor

Exterior

X Wet Areas

X Ramp/Entry

Splash Zones

# B

# **Stability**

Relevant NZBC Clause Product Performance

B2.3.1(c) 
Residential 
Commercial 
Industrial -

# C

#### **Protection from Fire**

Relevant NZBC Clause Product Performance

C3.4

C3.4 (a) Wall 
C3.4 (b) Floor -

# D

#### **Access**

Relevant NZBC Clause Product Performance

D1.3.3

Level Surface (Wet) 
Level Surface (Dry) 
Suitable for food prep -

# Ε

#### **Moisture**

Relevant NZBC Clause Product Performance

E3.3.3 Impervious and easily cleaned

E3.3.5 Impervious and easily cleaned

E3.3.6 Water resistant

NZBC/AS1 -

# F

# Safety of Users

 Relevant NZBC Clause
 Product Performance

 F2.3.1

 Phthalate-free

 Indoor Air Quality

# G

#### **Services and Facilities**

Relevant NZBC Clause Product Performance

G3.3.2 (b) Water resistant

G6.3.2 -

# Н

# **Energy Efficiency**

Relevant NZBC Clause Product Performance
Thermal Rating -

# X

## Warnings and Bans

Building Act 2004 Product Performance

Section 26 -

# **Supporting Documents**

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:291125

# Product Information Declaration Tredsafe DT031 Range

## B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

## E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

## G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

# **Note**

It is expected that **Tredsafe DT031** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:291125

# **Product Information Declaration Tredsafe DT031 Range**

# **Identifiers**

This JPID covers all colours from Tredsafe DT031 including:

Matte Black 40031 Bronze 40032 Brass 40033 Natural Satin 11955 Mill Finish 11954

# **Jacobsen**<sup>®</sup>

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN:

9429040403328



Product Manufacturer: **Tredsafe** Country of Origin: -

Page 3 of 3 V:291125