

## Product Information Declaration

# Tredsafe Inserts Subtle Colours Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as Tredsafe Inserts Subtle Colours

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

|  |   |   |   |
|--|---|---|---|
| <input checked="" type="checkbox"/> Residential            | <input checked="" type="checkbox"/> Commercial          | <input checked="" type="checkbox"/> Interior            | <input checked="" type="checkbox"/> Exterior    |
| <input checked="" type="checkbox"/> High Traffic           | <input checked="" type="checkbox"/> Low Traffic         | <input checked="" type="checkbox"/> Exposed Sunlight    | <input checked="" type="checkbox"/> Wet Areas   |
| <input checked="" type="checkbox"/> Antistatic Environment | <input checked="" type="checkbox"/> Food Prep Areas     | <input checked="" type="checkbox"/> Clean Room          | <input checked="" type="checkbox"/> With Wheels |
| <input checked="" type="checkbox"/> Ramp/Entry             | <input checked="" type="checkbox"/> Under Floor Heating | <input checked="" type="checkbox"/> Over Existing Floor |   |

## B Stability

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| B2.3.1(c)            | -                   |
| Residential          | -                   |
| Commercial           | 5 Years             |
| Industrial           | -                   |

## C Protection from Fire

| Relevant NZBC Clause | Product Performance              |
|----------------------|----------------------------------|
| C4.3                 |                                  |
| C4.3 (a) Wall        | CRF 10.3 kW/m2 (ISO 9239.1:2010) |
| C4.3 (b) Floor       | -                                |

## D Access

| Relevant NZBC Clause   | Product Performance         |
|------------------------|-----------------------------|
| D1.3.3                 |                             |
| Level Surface (Wet)    | SRV 47 (AS 4586:2013) - R11 |
| Level Surface (Dry)    | Acceptable Solution         |
| Suitable for food prep | -                           |

## E Moisture

| Relevant NZBC Clause | Product Performance           |
|----------------------|-------------------------------|
| E3.3.3               | Impervious and easily cleaned |
| E3.3.5               | Impervious and easily cleaned |
| E3.3.6               | Water resistant               |
| NZBC/AS1             | -                             |

## F Safety of Users

| Relevant NZBC Clause | Product Performance                 |
|----------------------|-------------------------------------|
| F2.3.1               | To be tested                        |
|                      | Does not encourage bacterial growth |
|                      | Phthalate-free                      |
| Indoor Air Quality   | -                                   |

## G Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b)           | Water resistant     |
| G6.3.2               | -                   |

## H Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| Thermal Rating       | Not tested          |

## X Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26        | True                |

## Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Tredsafe Inserts Subtle Colours Range

---

### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that Tredsafe Inserts Subtle Colours is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration

## Tredsafe Inserts Subtle Colours Range

### Identifiers

This JPID covers all colours from Tredsafe Inserts Subtle Colours including:

|                           |  |
|---------------------------|--|
| Burgundy - 112 12042      | Neutral Black - 106 12048                  |
| Royal Blue - 111 12041    | Rich Brown - 109 12077                     |
| Putty - 110 12040         | Light Grey - 108 12076                     |
| Rich Brown - 109 12039    | Mid Grey - 113 12098                       |
| Light Grey - 108 12038    | Jade Green - 114 12066                     |
| Neutral Black - 106 12091 | Mid Grey - 113 12065                       |
| Light Grey - 108 12060    | Burgundy - 112 12064                       |
| Charcoal Grey - 107 12059 | Jade Green - 114 12044                     |
| Neutral Black - 106 12058 | Mid Grey - 113 12043                       |
| Charcoal Grey - 107 12037 | Charcoal Grey - 107 12075                  |
| Neutral Black - 106 12036 | Neutral Black - 106 12074                  |
| Burgundy - 112 12097      | Royal Blue - 111 12063                     |
| Royal Blue - 111 12096    | Putty - 110 12062                          |
| Putty - 110 12095         | Rich Brown - 109 12061                     |
| Jade Green - 114 12082    | Royal Blue - 111 TS Insert Royal Blue 25mm |
| Mid Grey - 113 12081      | Rich Brown - 109 22940                     |
| Burgundy - 112 12080      | Putty - 110 TS insert putty 25mm           |
| Royal Blue - 111 12079    | Jade Green - 114 TS insert Jade Green 25mm |
| Putty - 110 12078         | Mid Grey - 113 19203                       |
| Rich Brown - 109 12094    | Light Grey - 108 22926                     |
| Light Grey - 108 12093    | Light Grey - 108 22926                     |
| Charcoal Grey - 107 12092 | Burgundy - 112 TS insert Burgundy 25mm     |
| Jade Green - 114 12099    |  |
| Charcoal Grey 25mm 12049  |  |

### Sustainability

| Rating System                           | Rating    | Product Performance |
|---|-----------|---------------------|
| Green Star Design & As Built NZ (V1)    | Credit 12 | -                   |
|   | Credit 20 | -                   |
|   | Credit 21 | -                   |
| Green Star Interiors NZ (V1)            | Credit 13 | -                   |
|   | Credit 20 | -                   |
|   | Credit 21 | -                   |
| Green Star Performance NZ (V1)          | Credit 21 | -                   |
|   |           |                     |
| Homestar V5                             | HC 7      | -                   |
|   | EN 3      | -                   |
| Homestar V4                             | Mat-1     | -                   |
|   | Mat-2     | -                   |
| Environmental Product Declaration (EPD) |           | -                   |
| Embodied Carbon Emission Data           |           | To be tested        |

### Environmental Credentials

# Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328



Product Manufacturer: Tredsafe  
Country of Origin: New Zealand