

Product Information Declaration

Shaw Contract Accent Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as Shaw Contract Accent

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

☐ Residential	☒ Commercial	☒ Interior	☐ Exterior
☒ High Traffic	☐ Low-Traffic	☒ Exposed Sunlight	☐ Wet Areas ¹
☐ Antistatic Environment	☐ Clean Room	☐ Over Existing Floor	☒ With Wheels
☐ Under Floor Heating	☐ Splash Zones ²	☐ Commercial Food Prep Areas	☐ Wet Areas ²
☐ Entrance			

1. Bathrooms with showers
2. Bathrooms without showers, laundries, kitchens, dining rooms adjacent to sanitary appliances with the right adhesive, and
- E3 Alternative installation instructions

B

Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	15 years
Residential	-
Commercial	Heavy Duty
Industrial	-

C

Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	-
C3.4 (b) Floor	CRF 5.8 kW/m2 (ISO 9239.1:2010)

D

Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	<0.5 mg/m3
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H

Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	-

X

Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](#) or by this QR code



Product Information Declaration

Shaw Contract Accent Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Shaw Contract Accent** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration

Shaw Contract Accent Range

Identifiers

This JPID covers all colours from Shaw Contract Accent including:

Daintree E41397	Paperbark E39357
Saltbush E39359	Kimberley Coast (Terracotta) E26751
River Gum 39358	Burdekin Plum (Carnelian) 26750
Murray Salt E39356	Ruby E26749
Mangrove E39355	Opal (Jasper) E26748
Kookaburra E39354	Great Sandy Desert (Tigers Eye) 26747
Kalgoorlie E39353	Galah (Shell) 26746
Jacaranda E39352	Eucalyptus (Sea Glass) 25431
Grampians E39351	Kakadu (Peridot) 26548
Cooper Pedy E39350	Red Ochre (Mesa) 26745
Cattlemen Denim E39349	Bells Beach (Blue Slate) 25432
Barossa Earth 39348	Blue Mountains (Azure) 26744
Banksia E39347	

Sustainability

Rating System	Rating	Product Performance
Green Star Buildings NZ	Responsible Product Value	25
	Exposure to Toxins	Tests available upon request
Green Star Design & As Built NZ (V1)	Credit 12	1 Point
	Credit 20	1 Point
	Credit 21	1 Point
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	1 Point
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		4.5kg CO2eq/m2 (Cradle to Gate)

Environmental Credentials



Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328

Product Manufacturer: **Shaw Contract**
Country of Origin: China