

## Product Information Declaration

# Shaw Contract Community Knotted Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as Shaw Contract Community Knotted

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Commercial	<input checked="" type="checkbox"/> Interior	<input checked="" type="checkbox"/> Exterior
<input checked="" type="checkbox"/> High Traffic	<input checked="" type="checkbox"/> Low-Traffic	<input checked="" type="checkbox"/> Exposed Sunlight	<input checked="" type="checkbox"/> Wet Areas
<input checked="" type="checkbox"/> Antistatic Environment	<input checked="" type="checkbox"/> Food-Prep Areas	<input checked="" type="checkbox"/> Clean-Room	<input checked="" type="checkbox"/> With Wheels
<input checked="" type="checkbox"/> Ramp/Entry	<input checked="" type="checkbox"/> Under-Floor Heating	<input checked="" type="checkbox"/> Over-Existing-Floor	

## B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	Lifetime Commercial Limited Warranty
Residential	-
Commercial	Heavy Duty
Industrial	-

## C Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CRF 6.4kW/m2 ( ISO 9239.1:2010)

## D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

## E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	≤0.5 mg/m3
	-
	Phthalate-free
Indoor Air Quality	Optimal

## G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

## H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

## X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

## Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Shaw Contract Community Knotted Range

---

### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that **Shaw Contract Community Knotted** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration

## Shaw Contract Community Knotted Range

### Identifiers

This JPID covers all colours from Shaw Contract Community Knotted including:

Wool 24386	Henna E5T301-1585
Souk E5T301-1500	Crafted E5T301-1580
Silver E5T301-1535	Blended E5T301-1555
Riad E5T301-1518	Argan 23641
Medina E5T301-1505	

### Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	1 Point
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Interiors NZ (V1)	Credit 13	1 Point
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		5.3kg Co2/m2 Cradle to Gate

### Environmental Credentials



## Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328

## ShawContract®

Product Manufacturer: Shaw Contract  
Country of Origin: United States of America