Product Information Declaration

Tarkett Desso Desert Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as **Tarkett Desso Desert**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

×	Residential	/	Commercial
/	High Traffic	×	Low Traffic
×	Antistatic Environment	×	Food Prop Areas

×	Low Traffic
×	Food Prep Areas
×	Under Floor Heating

<u> </u>	Interior
✓	Exposed Sunlight
×	Clean Room

X ExteriorX Wet Areas/ With Wheels

X Over Existing Floor

B

Stability

X Ramp/Entry

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	15 years	
Residential	23 Heavy (EN 1307)	
Commercial	33 Heavy	
Industrial	-	

C

Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CRF 8.4kW/m2 (ISO 9239.1:2010)

D

Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	-	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	-	

Е

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Gold (<100 μg / m3) (EN 16516)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance	
G3.3.2 (b)	Water resistant	
G6.3.2	24dB (ISO 10140)	

H

Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.071 m2.K/W (ISO 8302)



Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:300424

Product Information Declaration Tarkett Desso Desert Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Desso Desert** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:300424

Product Information Declaration Tarkett Desso Desert Range

Identifiers

This JPID covers all colours from Tarkett Desso Desert including:

AC89-2021 EAC89-2021	AC89-5402 EAC89-5402
AC89-9580 EAC89-9580	AC89-5121 EAC89-5121
AC89-9523 EAC89-9523	AC89-4413 EAC89-4413
AC89-9518 EAC89-9518	AC89-2928 EAC89-2928
AC89-8823 EAC89-8823	AC89-2914 EAC89-2914
AC89-8521 EAC89-8521	AC89-9516 EAC89-9516
AC89-8114 EAC89-8114	AC89-1321 EAC89-1321
AC89-7921 EAC89-7921	AC89-1914 EAC89-1914
AC89-7852 EAC89-7852	AC89-9508 EAC89-9508
AC89-7173 EAC89-7173	B882-9505 23592
AC89-6431 EAC89-6431	B882-8811 23591
AC89-2117 EAC89-2117	B882-8213 10242
AC89-9093 EAC89-9093	B882-7184 23910
AC89-8915 EAC89-8915	B882-9502 10279
AC89-6118 EAC89-6118	

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	1 Point
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	1 Point
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		4.95kg CO2eq/m2 (Cradle to Gate)

Environmental Credentials

























Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

Product Manufacturer: **Tarkett** Country of Origin: Netherlands

Page 3 of 3 V:300424