Jacobsen[®]


Product Information Declaration Serenity Shores Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as Serenity Shores

Scope and Limitations of Intended Use

~	Residential	~	Commercial
~	High Traffic	×	Low Traffic
×	Antistatic Environment	$\overline{\mathbf{x}}$	Food Prep Areas
×	Ramp/Entry	- x	Under Floor Heating



Identifiers

See individual sku codes under identifiers

Х **Over Existing Floor** X Exterior

Х Wet Areas

X With Wheels

В

Stability Relevant NZBC Clause **Product Performance** B2.3.1(c) Jacobsen Carpets are covered by the NZ

Consumer Guarantees Act of 1993. Residential Extra Heavy Duty - 6 star Commercial Medium Duty - 2 Star Industrial

С **Protection from Fire**

Relevant NZBC Clause **Product Performance** C3.4 C3.4 (a) Wall _ C3.4 (b) Floor CHF 5.3 kW/m2 (ISO 9239.1:2010)

D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	_

Suitable for food prep

Ε

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	Not Tested
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Good

G **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

Н **Energy Efficiency**

Relevant NZBC Clause		Product Performance	

Thermal Rating

Not tested

Х Warnings and Bans

Building Act 2004 **Product Performance**

Section 26

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration Serenity Shores Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

Note

It is expected that **Serenity Shores** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Product Information Declaration Serenity Shores Range

Identifiers

This JPID covers all colours from Serenity Shores including:

Raw Umber 406 24301 Oatmeal 405 24300 Mushroom 408 24299 Gunsmoke 404 24298 Gravel 403 24297 Ashen Grey 402 24296 Antique White 401 24295 Shoreliner 407 24517

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	-
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	-
Environmental Product Declara	-	
Embodied Carbon Emission Da	-	

Environmental Credentials



Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN: 9429040403328 Product Manufacturer: **Beaulieu** Country of Origin: Australia