#### **Product Information Declaration**

## **Shaw Contract Swerve Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as **Shaw Contract Swerve** 

#### **Identifiers**

Interior

See individual sku codes under identifiers

#### **Scope and Limitations of Intended Use**

×	Residential
<b>/</b>	High Traffic
$\overline{x}$	Antistatic Environment

Commercial
 Low Traffie
 Food Prep Areas

Exposed SunlightClean Room

Exterior
Wet Areas

With Wheels

X Ramp/Entry

X Under Floor Heating

**Cover Existing Floor** 

<del>-Floor</del>

#### R

#### **Stability**

Relevant NZBC Clause	Product Performance
B2.3.1(c)	5 Year Commercial Limited Warranty
Residential	-
Commercial	Heavy Duty
Industrial	-

#### **Protection from Fire**

Relevant NZBC Clause	Product Performance	
C3.4		
C3.4 (a) Wall	-	
C3.4 (b) Floor	36oz - 5.2 kW/m2 (ISO 9239.1:2010)	

#### **Access**

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	-	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	-	

#### F

#### Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	=

## F

#### **Safety of Users**

Relevant NZBC Clause	Product Performance	
F2.3.1	≤0.5 mg/m3	
	-	
	Phthalate-free	
Indoor Air Quality	Optimal	

### G

#### **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

## Н

#### **Energy Efficiency**

Relevant NZBC Clause	Product Performance	
Thermal Rating	Not tested	

## X

#### **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	-

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3

# **Product Information Declaration Shaw Contract Swerve Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

#### **Note**

It is expected that **Shaw Contract Swerve** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:030924

## **Product Information Declaration Shaw Contract Swerve Range**

#### **Identifiers**

This JPID covers all colours from Shaw Contract Swerve including:

High 11 ft Circle R051G-75500 Low 11 ft Circle R051G-75508 High 6 X 9 ft Rectangle R048G-75500 Low 12 x 15 ft Rectangle R050G-75508 High 8 X 10 ft Rectangle R049G-75500

High 12 x 15 ft Rectangle R050G-75500 Low 6 X 9 ft Rectangle R164G-75508 Low 8 X 10 ft Rectangle R049G-75508

#### **Sustainability**

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	1 Point
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star	Credit 13	1 Point
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Dec	-	
Embodied Carbon Emission	-	

#### **Environmental Credentials**





## **Jacobsen**<sup>®</sup>

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN:

9429040403328

# **ShawContract®**

Product Manufacturer: Shaw Contract Country of Origin: United States of America

Page 3 of 3 V:030924