Jacobsen®

Product Information Declaration

Tarkett Emme Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the linoleum range sold by Jacobsen as **Tarkett Emme**

Scope and Limitations of Intended Use

| ~ | Residential | ~ | Commercial |
|---|------------------------|---|---------------------|
| ~ | High Traffic | × | Low Traffic |
| × | Antistatic Environment | × | Food Prep Areas |
| × | Ramp/Entry | × | Under Floor Heating |

Interior Exposed Sunlight Clean Room

Identifiers

See individual sku codes under identifiers

X Over Existing Floor

- X Exterior
- X Wet Areas
- With Wheels

B

Stability

| Relevant NZBC Clause | Product Performance | |
|----------------------|---------------------|--|
| B2.3.1(c) | 10 years | |
| Residential | 23 (ISO 10874) | |
| Commercial | 34 (ISO 10874) | |
| Industrial | 43 (ISO 10874) | |

C Protection from Fire

| Relevant NZBC Clause | Product Performance |
|----------------------|------------------------------------|
| C4.3 | |
| C4.3 (a) Wall | - |
| C4.3 (b) Floor | CRF 5.4 kW/m2 (ISO 9239-1:2010) |

D Access

G

G3.3.2 (b)

G6.3.2

| Relevant NZBC Clause | Product Performance |
|------------------------|---------------------|
| D1.3.3 | |
| Level Surface (Wet) | - |
| Level Surface (Dry) | Acceptable Solution |
| Suitable for food prep | - |

Product Performance

delta Lw 6 dB (EN ISO

Water resistant

717-2)

Ε

Moisture

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------|
| E3.3.3 | Impervious and easily cleaned |
| E3.3.5 | Impervious and easily cleaned |
| E3.3.6 | Water resistant |
| NZBC/AS1 | - |

F

Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------------|
| F2.3.1 | Less than 10µg/m3 (ISO 16000-9) |
| | Does not encourage bacterial growth |
| | Phthalate-free |
| Indoor Air Quality | Optimal |

H Enorgy Efficiency

Energy Efficiency

| Relevant NZBC Clause | Product Performance | | |
|----------------------|------------------------|--|--|
| Thermal Rating | 0.015m2 K/W (EN 10456) | | |

X Warnings and Bans

Building Act 2004 Product Performance
Section 26 -

Supporting Documents

Services and Facilities

Relevant NZBC Clause

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration Tarkett Emme Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

Note

It is expected that **Tarkett Emme** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Product Information Declaration Tarkett Emme Range

Identifiers

This JPID covers all colours from Tarkett Emme including:

Velluto E14235203 Tobacco E14235730 Tan E14235719 Strawberry E14235763 Prussian E14235766 Pistachio E14235756 Pine E14235756 Pear E14235753 Nude E14235755 Koala E14235794 Jade E14235797 Ice E14235765 Gold E14235728 Fox E14235734 Ferro E14235205 Cinnamon E14235731 Cenere E14235201 Cemento E14235202 Cedar E14235732 Carolina E14235760 Berry E14235743 Aqua E14235759

Sustainability

| Rating System | Rating | Product Performance |
|--|-----------|----------------------------------|
| Green Star Design & | Credit 12 | - |
| As Built NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 1 |
| Green Star | Credit 13 | - |
| Interiors NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 1 |
| Green Star Performance NZ (V1) | Credit 21 | 1 Point |
| Homestar V5 | HC 7 | 1 Point |
| | EN 3 | 1.5 Points |
| Homestar V4 | Mat-1 | 2 Point |
| | Mat-2 | 1 Point |
| Environmental Product Deceleration (EPD) | | Yes |
| Embodied Carbon Emission Data | | -0,60 kgCO2e/m2 (Cradle to Gate) |

Environmental Credentials



Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328



Product Manufacturer: Tarkett Country of Origin: Italy