Product Information Declaration

Knight Tile Rigid Core Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the luxury vinyl tiles (lvt) range sold by Jacobsen as Knight Tile Rigid Core

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓	Residential	Commercial	✓ Interior	X Exterior
×	High Traffie	Low Traffic	X Exposed Sunlight	X Wet Areas
×	Antistatic Environment	Clean Room	✓ With Wheels	X Ramp/Entry
×	Commercial Food Prep Areas	Under Floor Heating	X Over Existing Floor	✓ Splash Zones

B

Stability

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	Lifetime Residential, 10 years Light Commercial	
Residential	23 (ISO 10874)	
Commercial	31 Moderate (ISO 10874)	
Industrial	-	

Protection from Fire

Relevant NZBC Clause	Product Performance	
C3.4		
C3.4 (a) Wall	Has not been tested	
C3.4 (b) Floor	-	

D

Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	-	
Level Surface (Dry)	Refer to Quick Guide Slip Tests - Knight Tile	
Suitable for food prep	-	

F

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Low VOC
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance	
G3.3.2 (b)	Water resistant	
G6.3.2	-	

Н

Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	-

X

Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:030425

Product Information Declaration Knight Tile Rigid Core Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Knight Tile Rigid Core** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:030425

Product Information Declaration Knight Tile Rigid Core Range

Identifiers

This JPID covers all colours from Knight Tile Rigid Core including:

Lime Washed Oak 1220mm x 180mm 28053

Mid Limed Oak 1220mm x 180mm 28052

Rose Washed Oak 1220mm x 180mm 28051

Pale Limed Oak 1220mm x 180mm 28050

Coastal Blackbutt 1220mm x 180mm 28049

Nordic Limed Oak 1220mm x 180mm 28048

Shadow Studio Oak 1220mm x 180mm 28047

Classic Spotted Gum 1220mm x 180mm 28046 Coastline Oak 1220mm x 180mm 28045 Traditional Character Oak 1220mm x 180mm 28044

Washed Character Oak 1220mm x 180mm 28043

Blond Character Oak 1220mm x 180mm 28042

Urban Spotted Gum 1220mm x 180mm 28041

Grey Limed Oak 1220mm x 180mm 28040

White Painted Oak 1220mm x 180mm 28039

Light Worn Oak 1220mm x 180mm 28038

Sustainability

Rating System Rating		Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	0.75 Points
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	0.75 Points
Green Star Credit 21 Performance NZ (V1)		1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		GD 8.91kg CO2 eq RC 14.98kg CO2 eq

Environmental Credentials



















Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN:

9429040403328



Product Manufacturer: **Karndean**Country of Origin: China

Page 3 of 3 V:030425