

## Product Information Declaration

# Karndean Van Gogh Plank Gluedown Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the luxury vinyl tiles (lvt) range sold by Jacobsen as Karndean Van Gogh Plank Gluedown

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

|  |   |   |   |
|--|---|---|---|
| <input checked="" type="checkbox"/> Residential            | <input checked="" type="checkbox"/> Commercial          | <input checked="" type="checkbox"/> Interior            | <input checked="" type="checkbox"/> Exterior    |
| <input checked="" type="checkbox"/> High Traffic           | <input checked="" type="checkbox"/> Low-Traffic         | <input checked="" type="checkbox"/> Exposed-Sunlight    | <input checked="" type="checkbox"/> Wet-Areas   |
| <input checked="" type="checkbox"/> Antistatic-Environment | <input checked="" type="checkbox"/> Food-Prep-Areas     | <input checked="" type="checkbox"/> Clean-Room          | <input checked="" type="checkbox"/> With Wheels |
| <input checked="" type="checkbox"/> Ramp/Entry             | <input checked="" type="checkbox"/> Under Floor Heating | <input checked="" type="checkbox"/> Over-Existing-Floor |   |

## B Stability

| Relevant NZBC Clause | Product Performance                       |
|----------------------|---|
| B2.3.1(c)            | Lifetime Residential, 15 years Commercial |
| Residential          | 23 (ISO 10874)                            |
| Commercial           | 33 Heavy (ISO 10874)                      |
| Industrial           | -   |

## C Protection from Fire

| Relevant NZBC Clause | Product Performance                    |
|----------------------|--|
| C3.4                 |  |
| C3.4 (a) Wall        | Has not been tested                    |
| C3.4 (b) Floor       | Less than 11.0 kW/m2 (ISO 9239.1:2010) |

## D Access

| Relevant NZBC Clause   | Product Performance   |
|------------------------|-----------------------|
| D1.3.3                 |                       |
| Level Surface (Wet)    | -                     |
| Level Surface (Dry)    | SRV 32 (AS 4586:2013) |
| Suitable for food prep | -                     |

## E Moisture

| Relevant NZBC Clause | Product Performance           |
|----------------------|-------------------------------|
| E3.3.3               | Impervious and easily cleaned |
| E3.3.5               | Impervious and easily cleaned |
| E3.3.6               | Water resistant               |
| NZBC/AS1             | -                             |

## F Safety of Users

| Relevant NZBC Clause | Product Performance                 |
|----------------------|-------------------------------------|
| F2.3.1               | Low VOC                             |
|                      | Does not encourage bacterial growth |
|                      | Phthalate-free                      |
| Indoor Air Quality   | Optimal                             |

## G Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b)           | Water resistant     |
| G6.3.2               | -                   |

## H Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| Thermal Rating       | -                   |

## X Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26        | -                   |

## Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Karndean Van Gogh Plank Gluedown Range

---

### **B2.3.1**

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### **C3.4**

Surface Linings

#### **(b)**

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### **D1.3.3**

Access routes shall:

#### **(d)**

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### **E3.3.3**

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### **E3.3.5**

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### **E3.3.6**

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### **F2.3.1**

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### **G3.3.2**

Spaces for food preparation and utensil washing shall have:

#### **(b)**

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### **G6.3.1**

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### **G6.3.2**

The Impact Insulation Class of floors shall be no less than 55.

### **H1**

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that Karndean Van Gogh Plank Gluedown is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration

## Karndeans Van Gogh Plank Gluedown Range

### Identifiers

This JPID covers all colours from Karndeans Van Gogh Plank Gluedown including:

|   |   |
|---|---|
| River Spotted Gum 1219mm x 178mm 28107    | Northern Spotted Gum 1219mm x 178mm 28098 |
| Eastern Blackbutt 1219mm x 178mm 28106    | Ebony 1219mm x 178mm 28117                |
| Washed Blackbutt 1219mm x 178mm 28105     | Classic Oak 1219mm x 178mm 28116          |
| Smoked Maple 1219mm x 178mm 28104         | French Oak 1219mm x 178mm 28115           |
| Natural Maple 1219mm x 178mm 28103        | Birch 1219mm x 178mm 28114                |
| Misty Grey Oak 1219mm x 178mm 28102       | Distressed Oak 1219mm x 178mm 28113       |
| Light Distressed Oak 1219mm x 178mm 28101 | Country Oak 1219mm x 178mm 28112          |
| Greige Oak 1219mm x 178mm 28100           | Tranquil Oak 1219mm x 178mm 28111         |
| Blush Oak 1219mm x 178mm 28099            | Nocturne Oak 1219mm x 178mm 28110         |
|   | Millstone Sycamore 1219mm x 178mm 28109   |
|   | Marron Elm 1219mm x 178mm 28108           |

### Sustainability

| Rating System                           | Rating      | Product Performance                  |
|---|-------------|--------------------------------------|
| Green Star Design & As Built NZ (V1)    | Credit 12   | -                                    |
|   | Credit 20   | 1 Point                              |
|   | Credit 21   | 0.75 Points                          |
| Green Star Interiors NZ (V1)            | Credit 13   | -                                    |
|   | Credit 20   | 1 Point                              |
|   | Credit 21   | 0.75 Points                          |
| Green Star Performance NZ (V1)          | Credit 21   | 1 Point                              |
|   | Homestar V5 | HC 7<br>EN 3                         |
| Homestar V4                             | Mat-1       | 2 Points                             |
|   | Mat-2       | 1 Point                              |
| Environmental Product Declaration (EPD) |             | Yes                                  |
| Embodied Carbon Emission Data           |             | GD 11.04kg CO2 eq, RC 15.27kg CO2 eq |

### Environmental Credentials



## Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328



Product Manufacturer: Karndeans  
Country of Origin: China