

Product Information Declaration

Tarkett Colour Splash Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the rubber range sold by Jacobsen as Tarkett Colour Splash

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Commercial	<input checked="" type="checkbox"/> Interior	<input checked="" type="checkbox"/> Exterior
<input checked="" type="checkbox"/> High Traffic	<input checked="" type="checkbox"/> Low Traffic	<input checked="" type="checkbox"/> Exposed Sunlight	<input checked="" type="checkbox"/> Wet Areas
<input checked="" type="checkbox"/> Antistatic Environment	<input checked="" type="checkbox"/> Food Prep Areas	<input checked="" type="checkbox"/> Clean Room	<input checked="" type="checkbox"/> With Wheels
<input checked="" type="checkbox"/> Ramp/Entry	<input checked="" type="checkbox"/> Under Floor Heating	<input checked="" type="checkbox"/> Over Existing Floor	

B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	5 Years Commercial Limited
Residential	-
Commercial	Heavy Duty
Industrial	-

C Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	>10.81 kW/m ² (ISO 9239.1:2010)

D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	ASTM D2047 - SCOF > 0.6
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 500 µg / m ³ Does not encourage bacterial growth Phthalate-free
Indoor Air Quality	Optimal

G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	ΔE ≤ 8.0 (ASTM F1514)

X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration

Tarkett Colour Splash Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that Tarkett Colour Splash is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration Tarkett Colour Splash Range

Identifiers

This JPID covers all colours from Tarkett Colour Splash including:

VE9 ANTELOPE VALLEY CS VE9	VH7 SPICY CLEMENTINE CS VH7
VE8 SANDSTORM CS VE8	VH6 JOCKEY'S RIDGE CS VH6
VE7 MT RAINIER CS VE7	VH5 HIGHBRIDGE TRAIL CS VH5
VE6 DUSTY PALOUSE CS VE6	VH4 GOLDEN FLASH CS VH4
VE5 SNOWCAP CS VE5	VH3 LIBERTY CS VH3
VK5 CAPE HATTERAS CS VK5	VH2 ADIRONDACK CS VH2
VJ3 DAWGS CS VJ3	VH1 MARINER CS VH1
VJ2 SAND SHORELINE CS VJ2	VG9 MARITIME CS VG9
VJ1 SAILOR CS VJ1	VG8 CANNON BEACH CS VG8
VH9 LAKE CHELAN CS VH9	VG7 ECHO LAKE CS VG7
VH8 ORANGE MARY CS VH8	VG6 CANARY CS VG6
VE4 HISTORIC CS VE4	VG5 RIDE THE DUCK CS VG5
VE3 SPOKANE WARM CS VE3	VG4 COUGAR CS VG4
VE2 LAKE SHORE CS VE2	VG3 IRONSIDES CS VG3
VE1 LAKE COUR D'ALENE CS VE1	VG2 DUNGENESS CRAB CS VG2
VK4 PERRYS BLUE CS VK4	VG1 FORKS FALLS CS VG1
VK3 THE PUGET SOUND CS VK3	VF9 BRYCE POINT CS VF9
VK2 BLOODY MARY ON THE LAKE CS VK2	VF8 COZY CANNON CS VF8
VK1 SAN JUAN CS VK1	VF7 CAPE MAY CS VF7
VJ9 TORCH LAKE CS VJ9	VF6 SANDHILL CRANE CS VF6
VJ8 PALOUS FALLS CS VJ8	VF5 GORGE AREA CS VF5
VJ7 OLD YORK CS VJ7	VF4 HUSK CS VF4
VJ6 DOUGLAS FIR CS VJ6	VF3 GREENBLUFF CS VF3
VJ5 VINEYARD CS VJ5	VF2 OAK ALLEY CS VF2
VJ4 PLYMOUTH ROCK CS VJ4	VF1 OCTOBERFEST CS VF1

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Performance NZ (V1)	Credit 21	1 Point
	Homestar V5	HC 7 EN 3
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Declaration (EPD)	Yes	
Embodied Carbon Emission Data	2mm - 7.55kg CO2 eq m2, 3.17mm - 12.5kg/CO2 eq m2	

Environmental Credentials



Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328

Tarkett

Product Manufacturer: Tarkett
Country of Origin: United States of America