

Product Information Declaration

Tarkett Solid Colours Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the rubber range sold by Jacobsen as Tarkett Solid Colours

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

| | | | |
|--|---|---|---|
| <input checked="" type="checkbox"/> Residential | <input checked="" type="checkbox"/> Commercial | <input checked="" type="checkbox"/> Interior | <input checked="" type="checkbox"/> Exterior |
| <input checked="" type="checkbox"/> High Traffic | <input checked="" type="checkbox"/> Low Traffic | <input checked="" type="checkbox"/> Exposed Sunlight | <input checked="" type="checkbox"/> Wet Areas |
| <input checked="" type="checkbox"/> Antistatic Environment | <input checked="" type="checkbox"/> Food Prep Areas | <input checked="" type="checkbox"/> Clean Room | <input checked="" type="checkbox"/> With Wheels |
| <input checked="" type="checkbox"/> Ramp/Entry | <input checked="" type="checkbox"/> Under Floor Heating | <input checked="" type="checkbox"/> Over Existing Floor | |

B Stability

| Relevant NZBC Clause | Product Performance |
|----------------------|----------------------------|
| B2.3.1(c) | 5 Years Commercial Limited |
| Residential | - |
| Commercial | Heavy Duty |
| Industrial | - |

C Protection from Fire

| Relevant NZBC Clause | Product Performance |
|----------------------|--|
| C4.3 | |
| C4.3 (a) Wall | - |
| C4.3 (b) Floor | >10.81 kW/m ² (ISO 9239.1:2010) |

D Access

| Relevant NZBC Clause | Product Performance |
|------------------------|-------------------------|
| D1.3.3 | |
| Level Surface (Wet) | ASTM D2047 - SCOF > 0.6 |
| Level Surface (Dry) | Acceptable Solution |
| Suitable for food prep | - |

E Moisture

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------|
| E3.3.3 | Impervious and easily cleaned |
| E3.3.5 | Impervious and easily cleaned |
| E3.3.6 | Water resistant |
| NZBC/AS1 | - |

F Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|--|
| F2.3.1 | ≤ 500 µg / m ³ Does not encourage bacterial growth Phthalate-free |
| Indoor Air Quality | Optimal |

G Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b) | Water resistant |
| G6.3.2 | - |

H Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|-----------------------|
| Thermal Rating | ΔE ≤ 8.0 (ASTM F1514) |

X Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26 | - |

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration

Tarkett Solid Colours Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that Tarkett Solid Colours is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration

Tarkett Solid Colours Range

Identifiers

This JPID covers all colours from Tarkett Solid Colours including:

| | |
|---------------------------|------------------------------------|
| TH2 Blue Intensity CS TH2 | 14 Tropical Storm CS 14 |
| TH1 Glenhaven CS TH1 | 08 Icicle CS 08 |
| TG9 Poetry Plum CS TG9 | TA9 Indigo CS TA9 |
| TG8 Spicy Chip CS TG8 | TA7 Rusty Nail CS TA7 |
| TG7 Canary CS TG7 | TA5 Colonial Grey CS TA5 |
| TG5 Macadamia CS TG5 | TA3 Castaway CS TA3 |
| 167 Fudge CS 167 | 101 Seaweed CS 101 |
| 59 Heather Green CS 59 | TB6 Flame CS TB6 |
| 58 Windsor Blue CS 58 | 92 Blue Lagoon CS 92 |
| 55 Silver Grey CS 55 | 86 Hunter Green CS 86 |
| 49 Beige CS 49 | 85 Burgundy CS 85 |
| 48 Grey CS 48 | 84 Blue Jeans CS 84 |
| 163 Salsa CS 163 | 80 Fawn CS 80 |
| 162 Sovereign CS 162 | 76 Cinnamon CS 76 |
| 15 Cabernet CS 15 | 73 Palm Leaf CS 73 |
| 151 Iguana CS 151 | 72 Harbour CS 72 |
| 150 Wetlands CS 150 | 71 Storm Cloud CS 71 |
| 132 Espresso CS 132 | 70 Bluest CS 70 |
| 130 Sisal CS 130 | 68 White Sand CS 68 |
| 129 Silk CS 129 | 63 Burnt Umber CS 63 |
| 121 Cement CS 121 | 62 Tangerine Tango CS 62 |
| 11 Canvas CS 11 | 28 Medium Grey CS 28 |
| TG1 Snowbound CS TG1 | 284 Ganache CS 284 |
| TB3 Dover CS TB3 | 283 Toast CS 283 |
| TB2 Boxwood CS TB2 | 282 Vaporize CS 282 |
| 83 Midnight CS 83 | 280 Shoreline CS 280 |
| 461 Wicker CS 461 | 27 Mist CS 27 |
| 44 Dark Brown CS 44 | 24 Grey Haze CS 24 |
| 293 Peacock CS 293 | 22 Pearl CS 22 |
| 262 Drizzle CS 262 | 21 Platinum CS 21 |
| 199 Dockside CS 199 | 20 Charcoal CS 20 |
| 197 Shaded CS 197 | 190 Greege CS 190 |
| 195 Ash CS 195 | 18 Navy Blue CS 18 |
| 149 Milk Chocolate CS 149 | 168 Thunder CS 168 |
| TG6 Mink CS TG6 | 79 Bone White CS 79 |
| TG3 Iron Mountain CS TG3 | 460 Cotton CS 460 |
| TG2 Shark Fin CS TG2 | 281 Grizzly CS 281 |
| TB4 Grapest CS TB4 | 276 Mystical CS 276 |
| TA8 Welsh Castle CS TA8 | 23 Vapor Grey CS 23 |
| TA2 Saddlebrook CS TA2 | 194 Antique White CS 194 |
| 47 Brown CS 47 | 192 Tidewater CS 192 |
| 469 Mystify CS 469 | 12 Hard Rock CS 12 |
| 45 Sandalwood CS 45 | 113 Chestnutty CS 113 |
| 42 Sable CS 42 | 107 Neutrality CS 107 |
| 41 Sea Breeze CS 41 | TH3 Inkwel CS TH3 |
| 40 Black CS 40 | TB1 Peppercorn CS TB1 |
| 38 Pewter CS 38 | TA6 Bedrock CS TA6 |
| 34 Almond CS 34 | TA4 Gateway CS TA4 |
| 33 Adobe Peach CS 33 | TA1 Tannery CS TA1 |
| 32 Pebble CS 32 | Metallic Black Pearl 82 CS M82 |
| 31 Zephyr CS 31 | Metallic Ironstone 178 CS M178 |
| 29 Moon Rock CS 29 | Metallic Sterling Silver 69 CS M69 |
| 106 Skinny Dip CS 106 | Metallic Steel 179 CS M179 |
| 09 Clay CS 09 | Either One 66 CS M66 |
| 01 Snow White CS 01 | Metallic Brass 176 CS M176 |
| TG4 Black Magic CS TG4 | Metallic Old Gold 67 CS M67 |
| 50 White CS 50 | Metallic White Pearl 77 CS M77 |
| 264 Grounded CS 264 | |

Sustainability

| Rating System | Rating | Product Performance |
|---|-------------|---|
| Green Star Design & As Built NZ (V1) | Credit 12 | - |
| | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 0.75 |
| Green Star Interiors NZ (V1) | Credit 13 | - |
| | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 0.75 |
| Green Star Performance NZ (V1) | Credit 21 | 1 Point |
| | Homestar V5 | HC 7 EN 3 |
| Homestar V4 | Mat-1 | 2 Points |
| | Mat-2 | 1 Point |
| Environmental Product Declaration (EPD) | Yes | |
| Embodied Carbon Emission Data | | 2mm - 7.55kg CO2 eq m2, 3.17mm - 12.5kg/CO2 eq m2 |

Environmental Credentials



Jacobsen[®]

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacoben.co.nz

NZBN:
9429040403328

Tarkett

Product Manufacturer: Tarkett
Country of Origin: United States of America