Jacobsen®

Product Information Declaration

Tarkett Solid Colours Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the rubber range sold by Jacobsen as **Tarkett Solid Colours**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✗ ~~Exterior~~
✓ High Traffic	✗ ~~Low Traffic~~	✓ Exposed Sunlight	✗ ~~Wet Areas~~
✗ ~~Antistatic Environment~~	✗ ~~Food Prep Areas~~	✗ ~~Clean Room~~	✓ With Wheels
✗ ~~Ramp/Entry~~	✗ ~~Under Floor Heating~~	✗ ~~Over Existing Floor~~	

B
Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	5 Years Commercial Limited
Residential	-
Commercial	Heavy Duty
Industrial	-

C
Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	-
C3.4 (b) Floor	>10.81 kW/m2 (ISO 9239.1:2010)

D
Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	ASTM D2047 - SCOF > 0.6
Suitable for food prep	-

E
Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F
Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 500 µg / m^3
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G
Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H
Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	ΔE ≤ 8.0 (ASTM F1514)

X
Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code

Product Information Declaration
Tarkett Solid Colours Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Solid Colours** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration
Tarkett Solid Colours Range

Identifiers

This JPID covers all colours from Tarkett Solid Colours including:

TH2 Blue Intensity CS TH2
TH1 Glenhaven CS TH1
TG9 Poetry Plum CS TG9
TG8 Spicy Chip CS TG8
TG7 Canary CS TG7
TG5 Macadamia CS TG5
167 Fudge CS 167
59 Heather Green CS 59
58 Windsor Blue CS 58
55 Silver Grey CS 55
49 Beige CS 49
48 Grey CS 48
163 Salsa CS 163
162 Sovereign CS 162
15 Cabernet CS 15
151 Iguana CS 151
150 Wetlands CS 150
132 Espresso CS 132
130 Sisal CS 130
129 Silk CS 129
121 Cement CS 121
11 Canvas CS 11
TG1 Snowbound CS TG1
TB3 Dover CS TB3
TB2 Boxwood CS TB2
83 Midnight CS 83
461 Wicker CS 461
44 Dark Brown CS 44
293 Peacock CS 293
262 Drizzle CS 262
199 Dockside CS 199
197 Shaded CS 197
195 Ash CS 195
149 Milk Chocolate CS 149
TG6 Mink CS TG6
TG3 Iron Mountain CS TG3
TG2 Shark Fin CS TG2
TB4 Grapest CS TB4
TA8 Welsh Castle CS TA8
TA2 Saddlebrook CS TA2
47 Brown CS 47
469 Mystify CS 469
45 Sandalwood CS 45
42 Sable CS 42
41 Sea Breeze CS 41
40 Black CS 40
38 Pewter CS 38
34 Almond CS 34
33 Adobe Peach CS 33
32 Pebble CS 32
31 Zephyr CS 31
29 Moon Rock CS 29
106 Skinny Dip CS 106
09 Clay CS 09
01 Snow White CS 01
TG4 Black Magic CS TG4
50 White CS 50
264 Grounded CS 264
14 Tropical Storm CS 14
08 Icicle CS 08
TA9 Indigo CS TA9
TA7 Rusty Nail CS TA7
TA5 Colonial Grey CS TA5
TA3 Castaway CS TA3
101 Seaweed CS 101
TB6 Flame CS TB6
92 Blue Lagoon CS 92
86 Hunter Green CS 86
85 Burgundy CS 85
84 Blue Jeans CS 84
80 Fawn CS 80
76 Cinnamon CS 76
73 Palm Leaf CS 73
72 Harbour CS 72
71 Storm Cloud CS 71
70 Bluest CS 70
68 White Sand CS 68
63 Burnt Umber CS 63
62 Tangerine Tango CS 62
28 Medium Grey CS 28
284 Ganache CS 284
283 Toast CS 283
282 Vaporize CS 282
280 Shoreline CS 280
27 Mist CS 27
24 Grey Haze CS 24
22 Pearl CS 22
21 Platinum CS 21
20 Charcoal CS 20
190 Greege CS 190
18 Navy Blue CS 18
168 Thunder CS 168
79 Bone White CS 79
460 Cotton CS 460
281 Grizzly CS 281
276 Mystical CS 276
23 Vapor Grey CS 23
194 Antique White CS 194
192 Tidewater CS 192
12 Hard Rock CS 12
113 Chestnutty CS 113
107 Neutrality CS 107
TH3 Inkwell CS TH3
TB1 Peppercorn CS TB1
TA6 Bedrock CS TA6
TA4 Gateway CS TA4
TA1 Tannery CS TA1
Metallic Black Pearl 82 CS M82
Metallic Ironstone 178 CS M178
Metallic Sterling Silver 69 CS M69
Metallic Steel 179 CS M179
Either One 66 CS M66
Metallic Brass 176 CS M176
Metallic Old Gold 67 CS M67
Metallic White Pearl 77 CS M77

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		2mm - 7.55kg CO2 eq m2, 3.17mm - 12.5kg/ CO2 eq m2

Environmental Credentials

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328

Product Manufacturer: **Tarkett**
Country of Origin: United States of America