# Jacobsen®

## **Product Information Declaration**


## **Tarkett Textures Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the rubber range sold by Jacobsen as **Tarkett Textures** 

#### Scope and Limitations of Intended Use

Residential	~	Commercial
High Traffic	×	Low Traffic
Antistatic Environment	×	Food Prep Areas
Ramp/Entry	×	Under Floor Heating



**Identifiers** 

See individual sku codes under identifiers

Over Existing Floor

X Exterior

X Wet Areas

With Wheels

## B

✓ | ✓ | × | ×

#### Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	5 Years Commercial Limited
Residential	-
Commercial	Heavy Duty
Industrial	-

#### **C** Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Refer to range
C4.3 (b) Floor	Refer to range

Х

### D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	Refer to range
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

### Ε

#### Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F

#### Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Refer to range
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Refer to range

## G

#### **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

### H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Refer to range

### **X** Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



## Product Information Declaration Tarkett Textures Range

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## Note

It is expected that **Tarkett Textures** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Product Information Declaration** Tarkett Textures Range

#### Identifiers

This JPID covers all colours from Tarkett Textures including:

Woven CS Woven	Leather
Linen CS Linen	Flagston
Brushed CS Brushed	Rice Pap
Circulinity Tricycle CS Tricycle	Cubis CS
Circulinity Round-A-Bout CS Round-A-	Circulini
Bout	Concrete
Circulinity Fastlane CS Fastlane	Bamboo
Circulinity Effervescent CS Effervescent	Diamono
Forged CS Forged	Wood Gi
Raised Square CS Raised Square	Smooth
Raised Round CS Raised Round	Hamme

eather CS Leather lagstone CS Flagstone lice Paper CS Rice Paper cubis CS Cubis Firculinity Tic-Tac-Toe CS Tic-Tac-Toe concrete CS Concrete famboo CS Bamboo Diamond CS Diamond Vood Grain CS Wood Grain mooth CS Smooth lammered CS Hammered

#### Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Performance NZ (V1)	Credit 21	2 Points
Homestar V5	HC 7	-
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	-
Environmental Product Dec	eleration (EPD)	Yes
Embodied Carbon Emission	n Data	-

#### **Environmental Credentials**



Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328



Product Manufacturer: **Tarkett** Country of Origin: United States of America