

Product Information Declaration

Tarkett Tapiflex Excellence 19dB Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Tapiflex Excellence 19dB

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✗ Exterior
✓ High Traffic	✗ Low Traffic	✓ Exposed Sunlight	✗ Wet Areas
✗ Antistatic Environment	✗ Clean Room	✓ With Wheels	✗ Ramp/Entry
✓ Commercial Food Prep Areas	✓ Under Floor Heating	✗ Over Existing Floor	✓ Splash Zones

B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	34 (ISO 18074)
Industrial	-

C Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	-
C3.4 (b) Floor	CRF 6.7 kW/m2 (ISO 9239-1:2010)

D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10 μ g/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	19 dB (ISO 717-2)

H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.04m2 K/W (ISO 10456)

X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration

Tarkett Tapiflex Excellence 19dB Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that Tarkett Tapiflex Excellence 19dB is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration

Tarkett Tapiflex Excellence 19dB Range

Identifiers

This JPID covers all colours from Tarkett Tapiflex Excellence 19dB including:

XXL Carrara Grande Natural E206047 096	Fragmento Deep Green E206017036
XXL Oak Tree Natural E206047 093	Fragmento Deep Brick E206017035
XXL Oak Tree Golden E206047 094	Fragmento Deep Black E206017034
Quadrillage Black & White E206017045	Esquisse Medium Grey E206017026
XXL Brecciastone Grey E206047 095	Matrix ² Light Grey E206017032
XXL Brecciacino Nude E206047 097	Matrix ² Dark Grey E206017031
Wood Chevron Beige E206017076	Granito Warm Grey E206017028
Variant Oak Warm Brown E206017089	Esquisse Light Grey E206017011
Variant Oak Nut E206017087	Esquisse Dark Grey E206017010
Terrazzo Grande Ochre E206017055	Encrypton Black & White E206017009
Terrazzo Grande Grey E206017054	Concrete Warm Grey E206017008
Terrazzo Grande Green E206017053	Concrete Ochre E206017025
Terrazzo Grande Brick E206017051	Concrete Grey Beige E206017006
Terrazzo Grande Deep Blue E206017052	Concrete Deep Blue E206017024
Variant Oak Natural E206017088	Concrete Dark Grey E206017005
Variant Oak Golden E206017086	Concrete Cool Grey E206017004
Variant Oak Brown Grey E206017085	Concrete Chalk E206017003
Variant Oak Beige E206017084	Concrete Brick E206017023
Uni White E206017075	Concrete Blue E206017022
Terrazzo Murano Gold & Silver E206017056	Chatillon Oak White E206017082
Uni Warm Grey E206017074	Chatillon Oak Natural E206017081
Terrazzo Concrete Grey E206017050	Chatillon Oak Light Brown E206017080
Terrazzo Concrete Black E206017049	Chatillon Oak Grey E206017079
Terrazzo Concrete Beige E206017048	Chatillon Oak Golden E206017078
Terrazzo Natural Grey E206017059	Chatillon Oak Beige E206017077
Tapped Metal Grey E206017015	Carpet White Grey E206017002
Uni Medium Grey E206017073	Carpet Ochre E206017021
Uni Intense Kaki E206017072	Carpet Moss E206017020
Uni Intense Brick E206017071	Carpet Intense Jean E206017001
Uni Intense Aqua E206017070	Carpet Dark Grey E206017019
Uni Deep Yellow E206017069	Carpet Brick E206017018
Uni Deep Red E206017068	Uni Deep Green E206017067
Tapped Metal Copper E206017047	Uni Deep Blue E206017066
Tapped Metal Brass E206017046	Uni Dark Grey E206017065
Scandinavian Oak Light Beige E206017014	Uni Dark Beige E206017064
Scandinavian Oak Dark Grey E206017013	Uni Black E206017063
Scandinavian Oak Beige E206017083	Tissage ² Soft Kaki E206017062
Plywood Natural E206017039	QR Code Soft Yellow E206017044
OSB Natural E206017033	QR Code Soft Sky Blue E206017043
Oak Tree Golden E206017091	QR Code Soft Grey E206017042
Oak Tree Beige E206017012	QR Code Soft Brick E206017041
Oak Longstripe Classical E206017090	QR Code Soft Aqua E206017040
Gommette Multico E206017027	Tissage ² Soft Grey E206017061
Fragmento Deep Yellow E206017038	Tissage ² Soft Grege E206017017
Fragmento Deep Turquoise E206017037	Tissage ² Soft Beige E206017016
	Tissage ² Soft Aqua E206017060
	Terrazzo Murano Terracotta & Copper E206017058
	Terrazzo Murano Petrol & Nude E206017057

Sustainability

Rating System	Rating	Product Performance
Green Star Buildings NZ	Responsible Product Value	27
	Exposure to Toxins	Meets minimum requirements
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		9.3 kgCO ₂ e / m ² (Cradle to Gate)

Environmental Credentials



