

## Product Information Declaration

# Tarkett Tapiflex Excellence Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Tapiflex Excellence

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Commercial	<input checked="" type="checkbox"/> Interior	<input checked="" type="checkbox"/> Exterior
<input checked="" type="checkbox"/> High Traffic	<input checked="" type="checkbox"/> Low Traffic	<input checked="" type="checkbox"/> Exposed Sunlight	<input checked="" type="checkbox"/> Wet Areas
<input checked="" type="checkbox"/> Antistatic Environment	<input checked="" type="checkbox"/> Food Prep Areas	<input checked="" type="checkbox"/> Clean Room	<input checked="" type="checkbox"/> With Wheels
<input checked="" type="checkbox"/> Ramp/Entry	<input checked="" type="checkbox"/> Under Floor Heating	<input checked="" type="checkbox"/> Over Existing Floor	

## B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	34 (ISO 18074)
Industrial	-

## C Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CRF 6.7 kW/m2 (ISO 9239-1:2010)

## D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	Refer to Summary Sheet
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

## E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10 µg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

## G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	19 dB (ISO 717-2)

## H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.04m2 K/W (ISO 10456)

## X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

### Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Tarkett Tapiflex Excellence Range

---

### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that Tarkett Tapiflex Excellence is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration

## Tarkett Tapiflex Excellence Range

### Identifiers

This JPID covers all colours from Tarkett Tapiflex Excellence including:

Scandinavian Oak Medium Grey E25134401	Intense Kaki E25136934
Scandinavian Oak Dark Grey E25134400	Bright Dark Turquoise E25136933
Esquisse Medium Grey E25133014	Bright Ice Blue E25136932
Esquisse Light Grey E25133013	Bright Anis E25136931
Grey Beige E25133012	Bright Yellow E25136930
Natural E25132818	Bright Orange E25136929
White E25132817	Facet Black & White E25133118
Beech Longstripe Light E25132102	Facet Fonte E25133117
Brushed Oak Light E25132027	Facet Mid Grey E25133116
Brushed Oak Medium E25132026	Facet Water E25133115
Tissage Soft Light Blue E25133130	Facet Yellow E25133113
Tissage Soft Beige E25133129	Granito Cool Grey E25133111
Tissage Soft Grege E25133128	Granito Warm Grey E25133110
Oak Tree Grey E25134202	Modern Maple E25133141
Oak Tree Beige E25134200	Indigo E25133140
Long Modern Oak Natural 19982	Turquoise E25133139
Long Modern Oak Grege E25134008	Dark Grey E25133138
Long Modern Oak White E25134005	Triangle Wood Natural E25133137
Steel Grey E25133601	Triangle Wood Chalk E25133136
Concrete Steel Blue E25133507	Fusion Lines Beige E25135173
Concrete Warm Grey E25133504	Fusion Lines Dark Grey E25135172
Matrix Dark Grey E25136019	Fusion Lines Phospho E25135171
Matrix Graphite E25136000	Cubic Intense Petrole E25135166
Intense Jean E25136943	Bright Red E25136928
Intense Terracotta E25136942	Bright Pink E25136927
Bright Extreme Blue E25136941	Bright Turquoise E25136926
White E25136940	Warm Grey E25136925
Black E25136939	Dark Beige E25136918
Intense Olive E25136938	Medium Grey E25136917
Intense Plum E25136937	Dark Grey E25136916
Oak Longstripe Natural E25132002	Granito Light Beige E25133109
Oak Longstripe Light E25132001	Carpet White Grey E25133108
Tissage Soft Grey E25133127	Carpet Intense Jean E25133107
Tapped Metal Grey E25133126	Carpet Intense Olive E25133106
Diamond Blue Green E25133124	Terrazzo Blue E25133105
Facet Prune E25133121	Terrazzo Terracotta E25133104
Concrete Grey Beige E25133503	Terrazzo Green E25133103
Concrete Chalk E25133502	Tissage Soft Water E25133134
Concrete Dark Grey E25133501	Tissage Soft Yellow E25133133
Concrete Cool Grey E25133500	Tissage Soft Light Green E25133131
Fiber Wood Natural E25133303	Bubbles Cold Mix E25135143
Fiber Wood Grege E25133302	Allover Wood White E25134714
Encrypton Black & White E25133189	Allover Wood Black E25134713
Flocons 2 Rainbow E25133170	Allover Wood Grege E25134711
Digital Wave Grey E25135183	Scandinavian Oak Medium Beige E25134403
Digital Wave Grey Ice Blue E25135182	Scandinavian Oak Light Beige E25134402
Origami Numbers Dark Grey E25135181	Matrix Bright Yellow E25136187
Fusion Lines Turquoise E25135176	Matrix Bright Anis E25136186
Intense Water E25136936	Matrix Bright Turquoise E25136185
Intense Petrole E25136935	Matrix Phospho E25136101
	Esquisse Dark Grey E25133015

### Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		9.3 kgCO <sub>2</sub> e / m <sup>2</sup> (Cradle to Gate)

### Environmental Credentials



