

Product Information Declaration

Tarkett Acczent Excellence Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Acczent Excellence

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✗ Exterior
✓ High Traffic	✗ Low-Traffic	✓ Exposed Sunlight	✗ Wet Areas
✗ Antistatic Environment	✗ Food-Prep Areas	✗ Clean-Room	✓ With Wheels
✗ Ramp/Entry	✓ Under Floor Heating	✗ Over Existing Floor	

B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	34 (ISO 18074)
Industrial	43 (ISO 18074)

C Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	-
C3.4 (b) Floor	CRF 8.12 kW/m2 (ISO 9239-1)

D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	Refer to Slip Test Summary Sheet
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10-µg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	delta Lw 3 dB (EN ISO 717-2)

H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.02m2 K/W (EN ISO 10456)

X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration

Tarkett Acczent Excellence Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that Tarkett Acczent Excellence is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration Tarkett Acczent Excellence Range

Identifiers

This JPID covers all colours from Tarkett Acczent Excellence including:

Carpet Intense Jean E206012001	Concrete Deep Blue E206012024
Wood Chevron Beige E206012076	Concrete Dark Grey E206012005
Variant Oak Warm Brown E206012089	Concrete Cool Grey E206012004
Variant Oak Nut E206012087	Concrete Chalk E206012003
Variant Oak Natural E206012088	Scandinavian Oak Beige E206012083
Variant Oak Golden E206012086	Quadrillage Black & White E206012045
Variant Oak Brown Grey E206012085	QR Code Soft Yellow E206012044
Variant Oak Beige E206012084	QR Code Soft Sky Blue E206012043
Uni White E206012075	QR Code Soft Grey E206012042
Uni Warm Grey E206012074	QR Code Soft Brick E206012041
Terrazzo Grande Grey E206012054	QR Code Soft Aqua E206012040
Terrazzo Grande Green E206012053	Plywood Natural E206012039
Terrazzo Grande Brick E206012051	Carpet Dark Grey E206012019
Terrazzo Grande Deep Blue E206012052	Carpet Brick E206012018
Terrazzo Concrete Grey E206012050	Uni Black E206012063
Uni Medium Grey E206012073	Tissage ² Soft Kaki E206012062
Uni Intense Kaki E206012072	Tissage ² Soft Grey E206012061
Uni Intense Brick E206012071	Tissage ² Soft Grege E206012017
Uni Intense Aqua E206012070	Tissage ² Soft Beige E206012016
Uni Deep Yellow E206012069	Concrete Brick E206012023
Fragmento Deep Turquoise E206012037	Concrete Blue E206012022
Fragmento Deep Green E206012036	Chatillon Oak White E206012082
Fragmento Deep Brick E206012035	Chatillon Oak Natural E206012081
Fragmento Deep Black E206012034	Chatillon Oak Light Brown E206012080
Esquisse Medium Grey E206012026	Chatillon Oak Grey E206012079
Terrazzo Concrete Black E206012049	Chatillon Oak Golden E206012078
Terrazzo Concrete Beige E206012048	Chatillon Oak Beige E206012077
Terrazzo Natural Grey E206012059	Carpet White Grey E206012002
Tapped Metal Grey E206012015	Carpet Ochre E206012021
Tapped Metal Copper E206012047	OSB Natural E206012033
Tapped Metal Brass E206012046	Oak Tree Golden E206012091
Scandinavian Oak Light Beige E206012014	Oak Tree Beige E206012012
Scandinavian Oak Dark Grey E206012013	Oak Longstripe Classical E206012090
Uni Deep Red E206012068	Matrix ² Light Grey E206012032
Uni Deep Green E206012067	Matrix ² Dark Grey E206012031
Uni Deep Blue E206012066	Granito Warm Grey E206012028
Uni Dark Grey E206012065	Gommette Multico E206012027
Uni Dark Beige E206012064	Fragmento Deep Yellow E206012038
Esquisse Light Grey E206012011	Tissage ² Soft Aqua E206012060
Esquisse Dark Grey E206012010	Terrazzo Murano Terracotta & Copper E206012058
Encrypton Black & White E206012009	Terrazzo Murano Petrol & Nude E206012057
Concrete Warm Grey E206012008	Terrazzo Murano Gold & Silver E206012056
Concrete Ochre E206012025	Terrazzo Grande Ochre E206012055
Concrete Grey Beige E206012006	Carpet Moss E206012020
	Concrete Grey Beige 19007

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Deceleration (EPD)	Yes	
Embodied Carbon Emission Data	8.78 kgCO ₂ e / m ² (Cradle to Gate)	

Environmental Credentials



Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328

Tarkett

Product Manufacturer: Tarkett
Country of Origin: France