

Product Information Declaration

Tarkett Eclipse Premium Spirit Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Eclipse Premium Spirit

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

☒ Residential	☒ Commercial	☒ Interior	☒ Exterior
☒ High Traffic	☒ Low-Traffic	☒ Exposed Sunlight	☒ Wet Areas ¹
☒ Antistatic Environment	☒ Clean Room	☒ Over Existing Floor	☒ With Wheels
☒ Under Floor Heating	☒ Splash Zones ²	☒ Commercial Food Prep Areas	☒ Wet Areas ²
☒ Entrance			

1. Bathrooms with showers
2. Bathrooms without showers, laundries, kitchens, dining rooms adjacent to sanitary appliances with the right adhesive, and
E3 Alternative installation instructions

B
Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 Years
Residential	-
Commercial	34 Very Heavy
Industrial	43 Heavy

C
Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	Group 3 (ISO 5660.1-2002)
C3.4 (b) Floor	CRF 10kW/m2 , (ISO 9239-1:2010)

D
Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	SRV 52 (AS 4586:2013)
Suitable for food prep	-

E
Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F
Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 10 µg/m3 (ISO 16000-9) Does not encourage bacterial growth Phthalate-free
Indoor Air Quality	Optimal

G
Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H
Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Approx. 0.01 m2 K/W

X
Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](#) or by this QR code



Product Information Declaration

Tarkett Eclipse Premium Spirit Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that Tarkett Eclipse Premium Spirit is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration

Tarkett Eclipse Premium Spirit Range

Identifiers

This JPID covers all colours from Tarkett Eclipse Premium Spirit including:

Dark Aqua 41184	Medium Blue 12324
Dark Blue 41183	Light Blue 12323
Light Sky Blue 41182	Light Green 12321
Red Purple 41175	Medium Warm Beige 12319
Dark Purple 41174	Yellow 12303
Brick 41173	MD Blue E21020730
Sand 41172	Dark Clay Grey 21147
Dark Sand 41171	Medium Grey 19099
Clay Brown 41170	Light Beige 12318
Lime Green 41181	Medium Cool Beige 12316
Green 41180	Light Cool Beige 12315
Light Orange 41179	Dark Cool Grey 12314
Orange 41178	Medium Cool Grey 12313
Red 41177	Grey 12312
Light Red 41176	Medium Pure Grey 12311
Midnight Blue 12308	Warm Grey 12301
Light Ocean Blue 12307	Black 12299
Ocean Blue 12306	Light Grey 12298
Dark Brick E21020768	Light Pure Grey 12310
Clay Grey 12328	Light Yellow E20809

Sustainability

Rating System	Rating	Product Performance
Green Star Buildings NZ	Responsible Product Value	21
	Exposure to Toxins	Meets minimum requirements
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		5.71 kgCO ₂ eq / m ² (Cradle to Gate)

Environmental Credentials



