

#### **Product Information Declaration**

## **Tarkett Eclipse Premium Spirit Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Eclipse Premium Spirit

#### **Identifiers**

X Over Existing Floor

See individual sku codes under identifiers

#### **Scope and Limitations of Intended Use**

×	Residential	<b>✓</b>	Commercial	<b>✓</b>	Interior	×	Exterior
~	High Traffic	×	<del>Low Traffic</del>	<b>✓</b>	Exposed Sunlight	×	<del>Wet Areas</del>
×	Antistatic Environment	~	Food Prep Areas	~	Clean Room	<b>✓</b>	With Wheels

#### R

#### **Stability**

X Ramp/Entry

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 Years
Residential	-
Commercial	34 Very Heavy
Industrial	43 Heavy

X Under Floor Heating

#### **Protection from Fire**

Relevant NZBC Clause	Product Performance		
C4.3			
C4.3 (a) Wall	Group 3 (ISO 5660.1-2002)		
C4.3 (b) Floor	CRF 10kW/m2 , (ISO 9239-1:2010)		

#### Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	SRV 52 (AS 4586:2013)
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

#### Ε

#### **Moisture**

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

#### F

#### **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 10 µg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

#### G

#### **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

### Н

#### **Energy Efficiency**

Relevant NZBC Clause	Product Performance	
Thermal Rating	Approx. 0.01 m2 K/W	

### X

#### **Warnings and Bans**

Building Act 2004	Product Performance		
Section 26	_		

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:040524

# **Product Information Declaration Tarkett Eclipse Premium Spirit Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

#### **Note**

It is expected that **Tarkett Eclipse Premium Spirit** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:040524

# **Product Information Declaration Tarkett Eclipse Premium Spirit Range**

#### **Identifiers**

This JPID covers all colours from Tarkett Eclipse Premium Spirit including:

Light Orange 23434 Orange 12309 Red 26506 Light Red 23210 Red Purple 25321 Midnight Blue 12308 Light Ocean Blue 12307 Ocean Blue 12306 Green 12305 Light Olive Green 23432 Dark Brick E21020768 Clay Grey 12328 Medium Blue 12324 Light Blue 12323 Medium Green 12322 Light Green 12321 Dark Warm Beige 12320 Medium Warm Beige 12319 Sand 12304

Yellow 12303 MD Blue E21020730 Dark Brown 12302 Dark Clay Grey 21147 Medium Grey 19099 Light Beige 12318 Medium Cool Beige 12316 Light Cool Beige 12315 Dark Cool Grey 12314 Medium Cool Grey 12313 Grey 12312 Medium Pure Grey 12311 Warm Grey 12301 Dark Warm Grey 12300 Black 12299 Light Grey 12298 Light Pure Grey 12310 Light Yellow 20809

#### **Sustainability**

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Deceleration (EPD)  Embodied Carbon Emission Data		Yes
		5.71 kgCO2eq / m2 (Cradle to Gate)

#### **Environmental Credentials**























## **Jacobsen®**

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

## **©** Tarkett

Product Manufacturer: Tarkett Country of Origin: Sweden

Page 3 of 3 V:040524