Product Information Declaration

Tarkett iQ Optima Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as **Tarkett iQ Optima**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

| <u>~</u> | Residential |
|----------|------------------------|
| <u> </u> | High Traffic |
| × | Antistatic Environment |

✓ Commercial

X Low Traffic

✓ Food Prep Areas

X Under Floor Heating

✓ Interior
✓ Exposed Sunlight
✓ Clean Room

★ Exterior✓ Wet Areas✓ With Wheels

X Over Existing Floor

B

Stability

X Ramp/Entry

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| B2.3.1(c) | 10 years |
| Residential | - |
| Commercial | 34 (ISO 18074) |
| Industrial | 43 (ISO 18074) |

C

Protection from Fire

| Relevant NZBC Clause | Product Performance | |
|----------------------|---------------------------------|--|
| C4.3 | | |
| C4.3 (a) Wall | Group 3 (ISO 5660.1-2015) | |
| C4.3 (b) Floor | CRF 9.2 kW/m2 (ISO 9239-1:2010) | |

D

Access

| Relevant NZBC Clause | Product Performance |
|------------------------|-----------------------|
| D1.3.3 | |
| Level Surface (Wet) | SRV 45 (AS 4586:2013) |
| Level Surface (Dry) | Acceptable Solution |
| Suitable for food prep | - |

Ε

Moisture

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------|
| E3.3.3 | Impervious and easily cleaned |
| E3.3.5 | Impervious and easily cleaned |
| E3.3.6 | Water resistant |
| NZRC/AS1 | |

F

Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------------|
| F2.3.1 | Less than 10¬μg/m3 (ISO 16000-9) |
| | Does not encourage bacterial growth |
| | Phthalate-free |
| Indoor Air Quality | Optimal |

G

Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b) | Water resistant |
| G6.3.2 | - |
| | |
| | |

Н

Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|-----------------------|
| Thermal Rating | 0.01m2 K/W (EN 12667) |



Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26 | - |

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:290424

Product Information Declaration Tarkett iQ Optima Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett iQ Optima** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:290424

Product Information Declaration Tarkett iQ Optima Range

Identifiers

This JPID covers all colours from Tarkett iQ Optima including:

White Grey 12506 Dark Grey 12505 Light Grey 12504 White 12503 Green 12502 Grey Beige 12501 Medium Blue 12500 Light Brown E3242249 Cool Light Beige E3242248 Light Gold Beige 21149 Light Sand Beige 12480 White Beige Grey 23066 Neutral Black 12479 Ice Blue 12499 Medium Grey 12498 Beige 12496 Dark Red Blue 12495 Light Red Blue 21816 Black 12494 Sage Green 12493 Neutral Dark Grey 12478 Neutral Grey 12477 Soft Cool Beige 12476 Soft Warm Beige 12475 Soft Dark Beige 12474 Soft Warm Grey E3242206 Soft Warm White 12473 Brown Yellow 12491 Light Yellow 12490 Medium Yellow E3242826

Yellow Beige 12489

Yellow 12488

Light Beige 12487 Medium Grey Beige 12486 Soft Dark Grey 12472 Soft Grey 12471 Soft Cool White 21267 Soft Dark Cool Grey 22790 Soft Cool Grey 22177 White Contrast (limited availability) 12521 Dark Brown 12515 Brown Beige 12514 Grey Brown 12513 GreyBeige 12512 Grey White 12511 Red 12485 Red Orange 12484 Orange 21564 Lilac 12483 Purple E3242255 Light Green E3242253 Dark Green 23068 Nature Brown 12520 Nature Beige 12519 Nature White 12518 Nature Black 12517 Nature Grey 12516 Dark Beige Grey 12509 Beige Grey 12508 Light Beige Grey 12507 Blue Green 12482 Blue 12481

Sustainability

| Rating System | Rating | Product Performance |
|--|-----------|-----------------------------------|
| Green Star Design & | Credit 12 | - |
| As Built NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 1 |
| Green Star | Credit 13 | - |
| Interiors NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 1 |
| Green Star Performance NZ (V1) | Credit 21 | 1 Point |
| Homestar V5 | HC 7 | 1 Point |
| | EN 3 | 1.5 Points |
| Homestar V4 | Mat-1 | 2 Point |
| | Mat-2 | 1 Point |
| Environmental Product Deceleration (EPD) | | Yes |
| Embodied Carbon Emission Data | | 5.24 kgCO2e / m2 (Cradle to Gate) |

Environmental Credentials

























Jacobsen[®]

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

© Tarkett

Product Manufacturer: **Tarkett** Country of Origin: Sweden

Page 3 of 3 V:290424