

## Product Information Declaration

# Tarkett Primo Premium Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Primo Premium

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

|  |   |   |   |
|--|---|---|---|
| <input checked="" type="checkbox"/> Residential            | <input checked="" type="checkbox"/> Commercial          | <input checked="" type="checkbox"/> Interior            | <input checked="" type="checkbox"/> Exterior    |
| <input checked="" type="checkbox"/> High Traffic           | <input checked="" type="checkbox"/> Low Traffic         | <input checked="" type="checkbox"/> Exposed Sunlight    | <input checked="" type="checkbox"/> Wet Areas   |
| <input checked="" type="checkbox"/> Antistatic Environment | <input checked="" type="checkbox"/> Food Prep Areas     | <input checked="" type="checkbox"/> Clean Room          | <input checked="" type="checkbox"/> With Wheels |
| <input checked="" type="checkbox"/> Ramp/Entry             | <input checked="" type="checkbox"/> Under Floor Heating | <input checked="" type="checkbox"/> Over Existing Floor |   |

## B Stability

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| B2.3.1(c)            | 10 years            |
| Residential          | 23 (ISO 10874)      |
| Commercial           | 34 (ISO 18074)      |
| Industrial           | 43 (ISO 18074)      |

## C Protection from Fire

| Relevant NZBC Clause | Product Performance                         |
|----------------------|---|
| C4.3                 |   |
| C4.3 (a) Wall        | Group 3 (ISO 5660.1-2015)                   |
| C4.3 (b) Floor       | CRF 10kW/m <sup>2</sup> , (ISO 9239-1:2010) |

## D Access

| Relevant NZBC Clause   | Product Performance   |
|------------------------|-----------------------|
| D1.3.3                 |                       |
| Level Surface (Wet)    | SRV 53 (AS 4586:2013) |
| Level Surface (Dry)    | Acceptable Solution   |
| Suitable for food prep | -                     |

## E Moisture

| Relevant NZBC Clause | Product Performance           |
|----------------------|-------------------------------|
| E3.3.3               | Impervious and easily cleaned |
| E3.3.5               | Impervious and easily cleaned |
| E3.3.6               | Water resistant               |
| NZBC/AS1             | -                             |

## F Safety of Users

| Relevant NZBC Clause | Product Performance                         |
|----------------------|---|
| F2.3.1               | Less than 10µg/m <sup>3</sup> (ISO 16000-9) |
|                      | Does not encourage bacterial growth         |
|                      | Phthalate-free                              |
| Indoor Air Quality   | Optimal                                     |

## G Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b)           | Water resistant     |
| G6.3.2               | -                   |

## H Energy Efficiency

| Relevant NZBC Clause | Product Performance               |
|----------------------|-----------------------------------|
| Thermal Rating       | 0.01m <sup>2</sup> K/W (EN 12667) |

## X Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26        | -                   |

### Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Tarkett Primo Premium Range

---

### **B2.3.1**

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### **C3.4**

Surface Linings

#### **(b)**

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### **D1.3.3**

Access routes shall:

#### **(d)**

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### **E3.3.3**

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### **E3.3.5**

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### **E3.3.6**

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### **F2.3.1**

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### **G3.3.2**

Spaces for food preparation and utensil washing shall have:

#### **(b)**

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### **G6.3.1**

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### **G6.3.2**

The Impact Insulation Class of floors shall be no less than 55.

### **H1**

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that Tarkett Primo Premium is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration Tarkett Primo Premium Range

## Identifiers

This JPID covers all colours from Tarkett Primo Premium including:

|                            |                           |
|----------------------------|---------------------------|
| Light Green 12549          | Dark Warm Beige 12538     |
| Clay Grey E21010625        | Medium Warm Beige 12537   |
| Medium Warm Grey E21010600 | Medium Cool Beige 12536   |
| Light Beige 12548          | Dark Warm Grey 12535      |
| Dark Cool Beige 12547      | Medium Grey Beige 12534   |
| Light Cool Beige 12546     | Black 12533               |
| Dark Cool Grey 12545       | Light Blue 12551          |
| Medium Cool Grey 12544     | Dark Green 12550          |
| Light Warm Grey 12543      | Medium Green 21330        |
| Medium Grey 12542          | Light Red 12532           |
| Medium Pure Grey 12541     | Grey 12531                |
| Soft Red E21010668         | Light Pure Grey 12530     |
| Soft Orange 21319          | Dark Orange 19107         |
| Dark Blue 12540            | White Olive Green 23078   |
| Medium Blue 12539          | Sky Blue 21317            |
| Soft Yellow E21010664      | Dark Brick Grey E21010632 |
| Soft Purple 21973          | Sand 21117                |
| Light Yellow 21318         |                           |

## Sustainability

| Rating System                           | Rating    | Product Performance  |
|---|-----------|--|
| Green Star Design & As Built NZ (V1)    | Credit 12 | -  |
|   | Credit 20 | 1 Point  |
|   | Credit 21 | Sustainability Factor (SF) = 1                             |
| Green Star Interiors NZ (V1)            | Credit 13 | -  |
|   | Credit 20 | 1 Point  |
|   | Credit 21 | Sustainability Factor (SF) = 1                             |
| Green Star Performance NZ (V1)          | Credit 21 | 1 Point  |
|   |           |  |
| Homestar V5                             | HC 7      | 1 Point  |
|   | EN 3      | 1.5 Points   |
| Homestar V4                             | Mat-1     | 2 Point  |
|   | Mat-2     | 1 Point  |
| Environmental Product Declaration (EPD) |           | Yes  |
| Embodied Carbon Emission Data           |           | 5.71 kgCO <sub>2</sub> e / m <sup>2</sup> (Cradle to Gate) |

## Environmental Credentials



## Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328

## Tarkett

Product Manufacturer: Tarkett  
Country of Origin: Sweden