

## Product Information Declaration

# Tarkett Primo Premium Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Primo Premium

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Commercial	<input checked="" type="checkbox"/> Interior	<input checked="" type="checkbox"/> Exterior
<input checked="" type="checkbox"/> High Traffic	<input checked="" type="checkbox"/> Low Traffic	<input checked="" type="checkbox"/> Exposed Sunlight	<input checked="" type="checkbox"/> Wet Areas
<input checked="" type="checkbox"/> Antistatic Environment	<input checked="" type="checkbox"/> Food Prep Areas	<input checked="" type="checkbox"/> Clean Room	<input checked="" type="checkbox"/> With Wheels
<input checked="" type="checkbox"/> Ramp/Entry	<input checked="" type="checkbox"/> Under Floor Heating	<input checked="" type="checkbox"/> Over Existing Floor	

## B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	23 (ISO 10874)
Commercial	34 (ISO 18074)
Industrial	43 (ISO 18074)

## C Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Group 3 (ISO 5660.1-2015)
C4.3 (b) Floor	CRF 10kW/m <sup>2</sup> , (ISO 9239-1:2010)

## D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	SRV 53 (AS 4586:2013)
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

## E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10µg/m <sup>3</sup> (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

## G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

## H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.01m <sup>2</sup> K/W (EN 12667)

## X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

### Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Tarkett Primo Premium Range

---

### **B2.3.1**

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### **C3.4**

Surface Linings

#### **(b)**

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### **D1.3.3**

Access routes shall:

#### **(d)**

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### **E3.3.3**

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### **E3.3.5**

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### **E3.3.6**

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### **F2.3.1**

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### **G3.3.2**

Spaces for food preparation and utensil washing shall have:

#### **(b)**

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### **G6.3.1**

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### **G6.3.2**

The Impact Insulation Class of floors shall be no less than 55.

### **H1**

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that Tarkett Primo Premium is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration Tarkett Primo Premium Range

## Identifiers

This JPID covers all colours from Tarkett Primo Premium including:

Light Green 12549	Dark Warm Beige 12538
Clay Grey E21010625	Medium Warm Beige 12537
Medium Warm Grey E21010600	Medium Cool Beige 12536
Light Beige 12548	Dark Warm Grey 12535
Dark Cool Beige 12547	Medium Grey Beige 12534
Light Cool Beige 12546	Black 12533
Dark Cool Grey 12545	Light Blue 12551
Medium Cool Grey 12544	Dark Green 12550
Light Warm Grey 12543	Medium Green 21330
Medium Grey 12542	Light Red 12532
Medium Pure Grey 12541	Grey 12531
Soft Red E21010668	Light Pure Grey 12530
Soft Orange 21319	Dark Orange 19107
Dark Blue 12540	White Olive Green 23078
Medium Blue 12539	Sky Blue 21317
Soft Yellow E21010664	Dark Brick Grey E21010632
Soft Purple 21973	Sand 21117
Light Yellow 21318	

## Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
	Homestar V5	HC 7 EN 3
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Declaration (EPD)	Yes	
Embodied Carbon Emission Data		5.71 kgCO <sub>2</sub> e / m <sup>2</sup> (Cradle to Gate)

## Environmental Credentials



## Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328

## Tarkett

Product Manufacturer: Tarkett  
Country of Origin: Sweden