Product Information Declaration

Tarkett Somplan 350 Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as **Tarkett Somplan 350**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

<u> </u>	Residential	
/	High Traffic	

Antistatic Environment

X Ramp/Entry

✓ Low Traffic

✓ Food Prep Areas

X Under Floor Heating

_	Interior	

✓ Exposed Sunlight

X Clean Room

X Over Existing Floor

Exterior

X Wet Areas

✓ With Wheels

R

Stability

 Relevant NZBC Clause
 Product Performance

 B2.3.1(c)
 10 years

 Residential

 Commercial
 34 (ISO 18074)

 Industrial
 43 (ISO 18074)

Protection from Fire

 Relevant NZBC Clause
 Product Performance

 C3.4

 C3.4 (a) Wall

 C3.4 (b) Floor
 CRF ≥11kW/m2 (ISO 9239-1:2010)

Access

Relevant NZBC Clause Product Performance

D1.3.3

Level Surface (Wet)
Level Surface (Dry) Acceptable Solution

Suitable for food prep -

Е

Moisture

Relevant NZBC Clause Product Performance

E3.3.3 Impervious and easily cleaned

E3.3.5 Impervious and easily cleaned

E3.3.6 Water resistant

NZBC/AS1 -

F

Safety of Users

Relevant NZBC Clause Product Performance

F2.3.1 - Does not encourage bacterial growth
Phthalate-free

Indoor Air Quality Optimal

G

Services and Facilities

Relevant NZBC Clause Product Performance
G3.3.2 (b) Water resistant
G6.3.2 -

Н

Energy Efficiency

Relevant NZBC Clause Product Performance
Thermal Rating -

X

Warnings and Bans

Building Act 2004 Product Performance

Section 26 -

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:301024

Product Information Declaration Tarkett Somplan 350 Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Somplan 350** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:301024

Product Information Declaration Tarkett Somplan 350 Range

Identifiers

This JPID covers all colours from Tarkett Somplan 350 including:

Middle Green 26728 Light Green 26727 Middle Blue 26726 Red 26725 Dark Orange 26724 Middle Warm Beige 26721 Middle Warm Grey 26720 Middle Cool Grey 26713 Light Cool Grey 26712 Peaceful Blue 26711 Middle Yellow 26710 Light Beige 26709

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	-
	Credit 21	Sustainability Factor (SF) = .5
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	-
	Credit 21	Sustainability Factor (SF) = 0.5
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Dec	-	
Embodied Carbon Emission	-	

Environmental Credentials

Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN: 9429040403328



Product Manufacturer: **Tarkett** Country of Origin: China

Page 3 of 3 V:301024