Product Information Declaration

Tarkett Standard Plus Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Standard Plus

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓	Residential		
_			

✓ High Traffic

✓ Antistatic Environment

X Ramp/Entry

X Low Traffic

✓ Food Prep Areas

Under Floor Heating

_	Intorior
,	Interior

✓ Exposed Sunlight

X Clean Room

X Over Existing Floor

Exterior

X Wet Areas

✓ With Wheels

R

Stability

Product Performance
10 years
-
34 (ISO 10581)
43 (ISO 10581)

Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Group 3 (ISO 5660.1-2015)
C4.3 (b) Floor	CRF 11 kW/m2, (ISO 9239-1)

D

Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	SRV 49 (AS 4586:2013)
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

Ε

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10¬μg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

Н

Energy Efficiency

Relevant NZBC Clause Product Performance

Thermal Rating Approx 0.01m2 K/W (EN 12667)



Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:270424

Product Information Declaration Tarkett Standard Plus Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Standard Plus** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:270424

Product Information Declaration Tarkett Standard Plus Range

Identifiers

This JPID covers all colours from Tarkett Standard Plus including:

Gold 12638
Sand Dark 12637
Sand Medium 12636
Sand 12635
Sand Light 12634
Medium Warm Grey 12633
Light Warm Grey 12632
Black 0500 12631
Dark Stone Grey 12630
Grey 12629
Light Grey 12628
Brown Grey 12627
Beige Grey 0495 12626
Light Beige Grey 12625
Dark Blue 12624

Medium Blue 12623 Red 12622 Yellow 12621 Sandstone 12620 Light Yellow Beige 12619 Stone Grey 12646 Pale Green 12645 Dark Beige 12618 Light Beige 12617 Lime 12644 Dark Green 12643 Light Blue 12641 Purple 12640 Orange 12639

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		5.69 kgCO2e / m2 (Cradle to Gate)

Environmental Credentials





















Jacobsen[®]

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

OTarkett

Product Manufacturer: Tarkett Country of Origin: Sweden

Page 3 of 3 V:270424