

Product Information Declaration

Tarkett Standard Plus Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Standard Plus

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✗ Exterior
✓ High Traffic	✗ Low Traffic	✓ Exposed Sunlight	✗ Wet Areas
✗ Antistatic Environment	✓ Food Prep Areas	✗ Clean Room	✓ With Wheels
✗ Ramp/Entry	✓ Under Floor Heating	✗ Over Existing Floor	

B

Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	34 (ISO 10581)
Industrial	43 (ISO 10581)

C

Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Group 3 (ISO 5660.1-2015)
C4.3 (b) Floor	CRF 11 kW/m2 , (ISO 9239-1)

D

Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	SRV 49 (AS 4586:2013)
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10µg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H

Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Approx 0.01m2 K/W (EN 12667)

X

Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](#) or by this QR code



# Product Information Declaration

## Tarkett Standard Plus Range

---

### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that **Tarkett Standard Plus** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration

## Tarkett Standard Plus Range

### Identifiers

This JPID covers all colours from Tarkett Standard Plus including:

Gold 12638	Medium Blue 12623
Sand Dark 12637	Red 12622
Sand Medium 12636	Yellow 12621
Sand 12635	Sandstone 12620
Sand Light 12634	Light Yellow Beige 12619
Medium Warm Grey 12633	Stone Grey 12646
Light Warm Grey 12632	Pale Green 12645
Black 0500 12631	Dark Beige 12618
Dark Stone Grey 12630	Light Beige 12617
Grey 12629	Lime 12644
Light Grey 12628	Dark Green 12643
Brown Grey 12627	Light Blue 12641
Beige Grey 0495 12626	Purple 12640
Light Beige Grey 12625	Orange 12639
Dark Blue 12624	

### Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Declaration (EPD)	Yes	
Embodied Carbon Emission Data	5.69 kgCO2e / m2 (Cradle to Gate)	

### Environmental Credentials



# Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328

# Tarkett

Product Manufacturer: Tarkett  
Country of Origin: Sweden