

Product Information Declaration

Tarkett Omnisport Profiles Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Omnisport Profiles

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

| X | Residential | × | Commercial | × | Interior | × | Exterior |
|---|----------------------------|---|---------------------|---|---------------------|---|--------------|
| × | High Traffie | × | Low Traffic | × | Exposed Sunlight | × | Wet Areas |
| × | Antistatic Environment | × | Clean Room | × | With Wheels | × | Ramp/Entry |
| × | Commercial Food Prep Areas | × | Under Floor Heating | × | Over Existing Floor | × | Splash Zones |

B

Stability

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| B2.3.1(c) | - |
| Residential | - |
| Commercial | - |
| Industrial | - |

Protection from Fire

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| C3.4 | |
| C3.4 (a) Wall | - |
| C3.4 (b) Floor | - |

D

Access

| Relevant NZBC Clause | Product Performance | | | |
|------------------------|---------------------|--|--|--|
| D1.3.3 | | | | |
| Level Surface (Wet) | - | | | |
| Level Surface (Dry) | - | | | |
| Suitable for food prep | - | | | |

E

Moisture

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------|
| E3.3.3 | Impervious and easily cleaned |
| E3.3.5 | Impervious and easily cleaned |
| E3.3.6 | Water resistant |
| NZBC/AS1 | - |

F

Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| F2.3.1 | - |
| | - |
| | Phthalate-free |
| Indoor Air Quality | - |

G

Services and Facilities

| Relevant NZBC Clause | Product Performance | | |
|----------------------|---------------------|--|--|
| G3.3.2 (b) | Water resistant | | |
| G6.3.2 | - | | |

Н

Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| Thermal Rating | - |

X

Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26 | - |

Supporting Documents

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:210225

Product Information Declaration Tarkett Omnisport Profiles Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Omnisport Profiles** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:210225

Product Information Declaration Tarkett Omnisport Profiles Range

Identifiers

This JPID covers all colours from Tarkett Omnisport Profiles including:

Pure Play 9.4mm TK-CV-OPP Active + 8.1mm TK-CV-OA Training 5.0mm TK-CV-OT Speed 3.45mm TK-CV-OS

Jacobsen[®]

Jacobsen 41 D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN:

9429040403328



Product Manufacturer: -Country of Origin: -

Page 3 of 3 V:210225