Product Information Declaration

Tarkett Omnisports Reference Multi-Use (6.2mm) Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Omnisports Reference Multi-Use (6.2mm)

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

×	Residential	✓	Commercial	✓	Interior	×	Exterior
~	High Traffic	×	Low Traffie	✓	Exposed Sunlight	×	Wet Areas
×	Antistatic Environment	×	Clean Room	~	With Wheels	×	Ramp/Entry
×	Commercial Food Prep Areas	×	Under Floor Heating	×	Over Existing Floor	~	Splash Zones

B

Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	-
Industrial	-

C

Protection from Fire

Relevant NZBC Clause	Product Performance
C3.4	
C3.4 (a) Wall	-
C3.4 (b) Floor	CRF 4.0 kW/m2 (ISO 9239-1:2010)

D

Access

Relevant NZBC Clause	Product Performance		
D1.3.3			
Level Surface (Wet)	-		
Level Surface (Dry)	Acceptable Solution		
Suitable for food prep	-		

Ε

Moisture

Relevant NZBC Clause	Product Performance		
E3.3.3	Impervious and easily cleaned		
E3.3.5	Impervious and easily cleaned		
E3.3.6	Water resistant		
NZBC/AS1	-		

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10¬Âμg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance		
G3.3.2 (b)	Water resistant		
G6.3.2	19dB		

Н

Energy Efficiency

Relevant NZBC Clause	Product Performance		
Thermal Rating	0.09m2 K/W (EN ISO 10456)		



Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:030425

Product Information Declaration Tarkett Omnisports Reference Multi-Use (6.2mm) Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Omnisports Reference Multi-Use (6.2mm)** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:030425

Product Information Declaration Tarkett Omnisports Reference Multi-Use (6.2mm) Range

Identifiers

This JPID covers all colours from Tarkett Omnisports Reference Multi-Use (6.2mm) including:

Concrete Deep Blue E8063
Uni Tonic Blue E8069
Uni Cranberry Pink E8062
Black Maple E8060
Table Tennis Tonic Red TK-CV-TT
Concrete Grey Beige E7063
Concrete Cool Grey E7061
Uni Silver Grey E8068
Nordic Oak E8067
Natural Oak E8066
Uni Kaki E8065
Uni Tonic Yellow E8073
Uni Tonic Red E8072

Uni Tonic Orange E8071
Uni Tonic Green E8070
Uni Black E19989
Golden Maple E19111
Uni Lagoon E26528034
Uni Coral E26528033
Uni Night Blue E26528024
Light Maple E23258
Uni Sky Blue E26528017
Uni Teal E26528015
Uni Grey E26528009
Grey Maple E26528005
Classic Oak E22192

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	-
	Credit 21	-
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	-
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	-
Environmental Product Dec	claration (EPD)	-
Embodied Carbon Emission	n Data	11.7 kgCO2e / m2 (Cradle to Gate)

Environmental Credentials

















Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN:

9429040403328



Product Manufacturer: Tarkett Country of Origin: France

Page 3 of 3 V:030425