

## Product Information Declaration

# Tarkett Protectwall 1.5mm Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Protectwall 1.5mm

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Commercial	<input checked="" type="checkbox"/> Interior	<input checked="" type="checkbox"/> Exterior
<input checked="" type="checkbox"/> High Traffic	<input checked="" type="checkbox"/> Low Traffic	<input checked="" type="checkbox"/> Exposed Sunlight	<input checked="" type="checkbox"/> Wet Areas
<input checked="" type="checkbox"/> Antistatic Environment	<input checked="" type="checkbox"/> Food Prep Areas	<input checked="" type="checkbox"/> Clean Room	<input checked="" type="checkbox"/> With Wheels
<input checked="" type="checkbox"/> Ramp/Entry	<input checked="" type="checkbox"/> Under-Floor Heating	<input checked="" type="checkbox"/> Over Existing Floor	

## B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	-
Industrial	-

## C Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Group 1s (EN13501)
C4.3 (b) Floor	-

## D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

## E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10 $\mu$ g/m <sup>3</sup> (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

## G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

## H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.01m <sup>2</sup> K/W (EN ISO 1254)

## X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

## Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Tarkett Protectwall 1.5mm Range

---

### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that Tarkett Protectwall 1.5mm is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration Tarkett Protectwall 1.5mm Range

## Identifiers

This JPID covers all colours from Tarkett Protectwall 1.5mm including:

Uni White Grey (new 2022) 23402	Tisse-Grey Beige 23413
Uni-Warm Grey 23407	Tisse-Fresh Green 23400
Uni-Super White (new 2022) 23443	Jungle-Tonic 23436
Uni-Light Grey 23398	Jungle-Grey 23437
Uni-Light Beige 23399	Jungle-Green Celadon 23449
Uni-Bright Ice Blue 23410	Jungle-Beige 23439
Transition-Grey 23417	Concrete-Cool Grey 23414
Transition-Blue Green 23415	Concrete-Chalk 23404
Tisse-White Blue 23412	Tisse-Grey 23396
Tisse-Warm Grey 23397	Tisse-Light Grey 23395
Tisse-Light Yellow 23411	Marble Carrare 23416
Tisse-Light Aqua 23401	

## Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Declaration (EPD)		Yes
Embodied Carbon Emission Data		7.04 kgCO <sub>2</sub> e / m <sup>2</sup> (Cradle to Gate)

## Environmental Credentials



## Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328

## Tarkett

Product Manufacturer: Tarkett  
Country of Origin: Luxembourg