

VINYL
HETEROGENEOUS

ACCZENT
EXCELLENCE
RUBY



Extra performance with extra safety touch.

Acczent Excellence Ruby is a compact heterogeneous vinyl flooring developed for all heavy traffic commercial areas such as hospitals and schools. The 0.7mm pure PVC wear layer that is reinforced with TopClean™ PUR surface treatment, brings excellent resistance to indentation and abrasion, scuffing, scratches and stains. TopClean™ PUR surface treatment reduces the cost of cleaning and maintenance enabling a fast return on investment. Acczent Excellence Ruby requires no wax nor polish throughout its lifetime and significantly reduces the use of water, energy and chemical detergents for a better environmental footprint.

The 19 colour range has the latest trend colour and design options to effectively address the education and aged care segments.



Product Characteristics	Standards	Accent Excellence Ruby
Product construction	EN ISO 10582	Heterogeneous compact vinyl flooring
Classification	EN ISO 10874	Commercial: 34; Industrial: 43
Surface treatment		TopClean™ PUR
Total thickness	EN ISO 24346	2.0mm
Wear layer thickness	EN ISO 24340	0.7mm
Total weight	EN ISO 23997	3000 g/m ²
Form of delivery	EN ISO 24341	Approx. 23Lm x 2m
Warranty		10 years
Underfloor heating		Suitable
Colours		19

Performance Characteristics	Standards	Accent Excellence Ruby
Reaction to fire	AS ISO 9239-1	Critical radiant flux 8.2 kW/m ² Smoke 193%.min
Slip resistance	AS 4586/ DIN 51130*	P3/R10
Electrostatic Properties	EN 1815/ EN 1081	< 2 kV on concrete/ R1 > 10 ⁹ Ω
Total VOC emissions	AgBB/DIBt	≤ 100 µg/m ³ (after 28 days)
Thermal resistance	EN 12667	0.02 m ² K/W
Chemical resistance	EN IS 26987	High resistance
Dimensional stability	EN ISO 23999	≤ 0.10%
Wear-layer binder content	EN ISO 10582	Type I
Residual indentation	EN ISO 24343-1	≤ 0.02mm
Castor chair test	ISO 4918	No damage
Furniture leg test	EN 424	No damage
Curl resistance to heat	EN ISO 23999	≤ 8mm
Light fastness	EN ISO 105-B02	≥ 6

* DIN 51130.2004 and 2010 is equivalent to Appendix D AS 4586.2013

Recommended specification clauses for your project

Tarkett product number starting with 2509.

- 2.0mm gauge with minimum 0.7mm wear layer, 2m wide glass fibre reinforced
- Heterogeneous vinyl floor covering
- TVOC below 100 µg/ m³
- Residual indentation ≤ 0.02mm to EN ISO 24343-1
- Use area classification of 34, 43 to EN ISO 10874
- Manufactured in a plant with certification to ISO 9001 and ISO14001
- 10 year commercial manufacturer's product warranty
- Must be installed as per manufacturer's instructions and as per AS 1884 with matching weldrod on seams/ joins

For information on our full range, contact us on 1300 851 484
or visit Tarkospec.com.au

The information in this data sheet is correct at date of publication however, due to Tarkett's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Tarkett's instructions regarding installation, cleaning and maintenance must be observed. Please contact Tarkett for further information on these instructions.