








| | ACCOLADE PLUS | ACCOLADE FOOHOLD | ACCOLADE SAFE | WALLFLEX |
|--------------|---|--|---|---|
| Practical | <ul style="list-style-type: none"> Exclusive homogeneous formulation including replenishing polyurethane throughout the thickness of the floor. Protective polyurethane finish reduces initial and ongoing maintenance and increases scuff resistance. | <ul style="list-style-type: none"> Polyurethane reinforced surface featuring PUR² technology to aid maintenance and provide additional resistance against staining. Exclusive homogeneous formulation including replenishing polyurethane throughout the thickness of the floor. Colours mix and match with Accolade Safe & Accolade Plus. | <ul style="list-style-type: none"> Offers supreme safety without the impregnated silicon chips of conventional non-slip resistant flooring that can attract and hold dirt, increasing maintenance and wear and tear on cleaning equipment. Unique construction with highly accented jasje (multi-colour chip) visual helps mask dirt and wear patterns. | <ul style="list-style-type: none"> Polyurethane coating aids maintenance. Clean, simple design for an uncomplicated look or the addition of a frieze if desired. 1.5 metre width ideal dado height for ease of installation. 2.0mm to align with floor vinyl. |
| Durable | <ul style="list-style-type: none"> Homogeneous construction for excellent dent and gouge resistance. The embossed surface texture and highly accented jasje (multi-colour chip) visual help hide dirt and wear patterns created in high traffic conditions. | <ul style="list-style-type: none"> Combination of embossed surface, aluminium oxide and polyurethane provides added slip resistance and protects long term appearance. Homogeneous construction for excellent durability and indentation resistance. | <ul style="list-style-type: none"> The embossed surface reduces aquaplaning, while aiding slip resistance. | <ul style="list-style-type: none"> Polyurethane coating reduces maintenance costs and protects long term appearance. Homogeneous construction for excellent dent and gouge resistance. 2.0mm thick for improved indent resistance. |
| Applications | <ul style="list-style-type: none"> Hospital Aged Care Health Care Education Light Industrial Mercantile Hospitality | Recommended for wet barefoot areas of <ul style="list-style-type: none"> Hospital Aged Care Health Care Education | <ul style="list-style-type: none"> Hospital Aged Care Health Care Education Light Industrial Mercantile Hospitality | <ul style="list-style-type: none"> Hospital Aged Care Health Care Education Light Industrial Mercantile Hospitality |

PLEASE NOTE: Recommendations are for guidance only, refer to relevant local, state and federal construction codes and standards for requirements

| TECHNICAL DATA | | ACCOLADE PLUS | ACCOLADE FOOHOLD | ACCOLADE SAFE | WALLFLEX |
|--------------------------------------|-------------|---|---|---|-------------------------|
| Type of floor covering/wall covering | ISO 10581 | Homogeneous sheet vinyl | Homogeneous sheet vinyl | Homogeneous sheet vinyl | Homogeneous sheet vinyl |
| Manufactured in | | Australia | Australia | Australia | Australia |
| Overall Thickness | ISO 24346 | 2.0mm | 2.0mm | 2.0mm | 2.0mm |
| Wear Layer thickness | ISO 24340 | 2.0mm | 2.0mm | 2.0mm | 2.0mm |
| Roll dimensions | ISO 24341 | 1.83m x 16m | 1.83m x 16m | 1.83m x 16m | 1.5m x 20m |
| Polyurethane Reinforced | | Yes PUR | Yes PUR | No | Yes PUR |
| Binder Content | ISO 10581 | Type 1 | Type 1 | Type 1 | Type 2 |
| Wear resistance | EN 660-2 | Group T | Group P | Group P | N/A |
| Slip Resistance | AS 4586 | | | | |
| Appendix A: Wet pendulum | | P3* | P4 | P4* | N/A |
| Appendix C: Wet/barefoot | | | B* | B* | |
| Appendix D: Oil-wet | | R10* | R11* | R10* | |
| Fire Resistance (Flooring) | ISO 9239-1 | | | | |
| Critical Radiant Flux | | ≥8kW/m ² | ≥8kW/m ² | ≥8kW/m ² | N/A |
| Smoke Development Rate | | ≤750%. minutes | ≤750%. minutes | ≤750%. minutes | |
| Fire Resistance (Walling) | AS/NZS 3837 | | | | |
| Cone Calorimeter | | Group 3 | Group 3 | Group 3 | Group 1 |
| Average specific extinction area | | <250m ² /kg | <250m ² /kg | <250m ² /kg | <250m ² /kg |
| Classification (Use Area) | ISO 10874 | Commercial: 34 | Commercial: 34 | Commercial: 34 | N/A |
| | |  |  |  | |
| | | Light Industrial: 43 | Light Industrial: 43 | Light Industrial: 43 | N/A |
| | |  |  |  | |

PLEASE NOTE: For Infinity & Infinity Custom minimum order quantities apply. Contact your Sales Representative or call 1800 632 624 for more information.

*For details refer to individual third party certificates.



Visit www.armstrongflooring.com.au or contact Customer Service 1800 632 624 for technical data, installation, cleaning and maintenance instructions.