

# Declare.

## Aspecta™ Elemental Dryback 2.5 mm x 0.55 mm HMTX Commercial

**Final Assembly:** Zhangjiagang, Jiangsu, China

**Life Expectancy:** 10 Year(s)

**Embodied Carbon:** 8.478 KG CO<sub>2</sub>-EQ ■

**Declared Unit:** 1 SQUARE METER OF FLOORING

**End of Life Options:** Landfill (100%)

### Ingredients:

Calcium carbonate; **Polyvinyl chloride**; Di(2-ethylhexyl) terephthalate; 2-Propenoic acid, 2-methyl-, polymer with butyl 2-propenoate and methyl 2-methyl-2-propenoate; Octadecanoic acid, calcium salt; Octadecanoic acid, zinc salt; 2-Propenoic acid, 2-(hydroxymethyl)-2-[[[1-oxo-2-propenyl)oxy]methyl]-1,3-propanediyl ester; Carbon black; 1,6-Hexanediol Diacrylate; Polyurethane foams; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Dipropylene Glycol Diacrylate; Silica gel, pptd., cryst.-free; C.I.Pigment Red 221; Vinyl chloride-vinyl acetate copolymers

### Living Building Challenge Criteria:

#### I-13 Red List:

- |  |                             |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free     | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared   |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

ASP-0024

EXP. 01 NOV 2025

Original Issue Date: 2019