



**JACOBSEN
BRINGS YOU**

**Aspecta
Elemental XL
Planks**

Luxury Vinyl Tile

Suitable for all residential and commercial applications such as:

- > Healthcare
- > Retail
- > Education
- > House
- > Workplace
- > Cafe
- > Restaurant

Technical Data	Standard	Result
Construction		Solid vinyl tile
Surface Treatment		Duraspect™ polymer finish
Residual Indentation	EN ISO 24343-1	≤0.1mm - Pass
Dimensional Stability	EN ISO 23999	≤0.25% - Pass
Colour Fastness to Light	ISO 105-B02	≥Grade 6 - Pass
Castor Chair Test	ISO 4918	Pass
Chemical Resistance	EN ISO 26987	No change
Thermal Resistance	EN ISO 12667	0.01745m ² K/W at 10° C
Abrasion / Wear Resistance	EN ISO 660-2	Fv ≤2.00mm ³ /100r
Static Electrical Propensity	EN 1815	≤2.0kV
Fire Test CRF	EN ISO 9239-1:2010	9.8 kW/m ²
Slip Resistance SRV	AS 4586	SRV 41



Prespa

Lomond

Constance

Maggiore

Lugano

Brienz

Como

Onega

Albano

Bolsena Herringbone

Bolsena Plank

Bolsena Chevron

Packaging Details

	Elemental XL 2.5mm Plank	Elemental 2.5mm Chevron	Elemental 2.5mm Herringbone	Elemental XL 5.0mm Plank
Size	1524mm x 228.6mm	690mm x 115mm	762mm x 152.4mm	1524mm x 228.6mm
Wear Layer	0.55mm	0.55mm	0.55mm	0.50mm
Edge Detail	4 sides Micro Bevel Edge			
Thickness	2.5mm	2.5mm	2.5mm	5.0mm
Pieces/Carton	10	36	24	4
Coverage/ Carton	3.48m ²	2.86m ²	2.79m ²	1.74m ²
Warranty	15 year Commercial and 20 year Residential			

Benefits:

Environmental certification - EPD, Declare, Floorscore, Eurofins Low VOC
Planks stocked in 2.5mm and 5.0mm thickness
Specific planks for Chevron or Herringbone design work in 2.5mm only
Extra large plank format
Four sided micro bevel
In Register surface embossing
Glue down installation
Heavy duty wear layer
Can be installed in kitchens and bathrooms

Jacobsen®



Talk to one of our experts, or visit our website:

0800 800 460 | jacobsen.co.nz | customer.services@jacobsen.co.nz

