



Aspecta One, Luxury Vinyl Tile Residential & Commercial

Suitable for all residential and commercial applications such as:

- > Healthcare
- > House
- > Cafe
- > Retail
- > Workplace
- > Restaurant
- > Education

609.6 x 609.6mm



Technical Data

Characteristic	Standard	
Construction	Solid Vinyl Tile	
Surface Treatment	Urethane coating with ceramic bead particles	
Overall Thickness	EN ISO 24346	2.5mm
Wear Layer Thickness	EN ISO 24340	0.70mm
Residual Indentation	EN ISO 24343-1	Pass
Dimensional Stability	EN ISO 23999	Pass
Colour Fastness to Light	ATSM F1515	Pass
Castor Chair Test	EN ISO 4918	No Change
Critical Radiant Flux	EN ISO 9239-1	9.8 kW/m ²
Chemical Resistance	No Change	
Slip Resistance	Dependent on surface finish. Refer to website.	
Environmental	Phthalate Free Low VOC Declare - SVHC Free	

Benefits

- Declare - SVHC free.
- Mini plank available for additional design work such as herringbone, chevron, basketweave.
- Four-sided micro bevel.
- Glue down installation.
- Extra heavy duty wear layer.
- Can be installed in kitchens and bathrooms.

Size & Packaging / Slip Resistance Value

	Size (mm)	Tiles Per Pack	m ² Per Pack	SRV
Midtown	609.6 x 609.6	9	3.34	41

Jacobsen® |  **ASPECTA™**
A NEW DIMENSION IN FLOORING

Talk to one of our experts, or visit our website:

0800 800 460 | customer.services@jacobsen.co.nz | jacobsen.co.nz

