

EBB RETREAT

Carpet Tile Specifications

CONSTRUCTION
PILE FIBER
TUFTING GAUGE
PILE HEIGHT
TOTAL CARPET WEIGHT
BACKING STRUCTURE
PILE TREATMENT
STANDARD MODULE SIZE

Performance

END USE CLASSIFICATION
CASTER CHAIR INDEX
DIMENSIONAL STABILITY
ELECTROSTATIC PROPENSITY
COLORFASTNESS TO LIGHT
INDOOR AIR QUALITY

Flammability

HOT METAL NUT
RADIANT PANEL TEST
SMOKE DENSITY
SURFACE FLAMMABILITY

Sound Absorption

NOISE REDUCTION COEFFICIENT
-----------------------------

EcoSoft®



Multi Level Texture Tufted  
100% Solution Dyed Nylon  
1/12 inch  
3.0 - 5.5 mm.  
2,880 gram/sq.m.  
 Recycled PET Cushion Back  
Stain and Soil Protection  
25 x 100 cm.

BS EN 1307 Class 33 - Heavy Commercial  
BS EN 985 ≥ 3,5  
BS EN 986 < 0.15%  
AATOC 134 < 3 KV  
ISO 105 B02 Min L6  
GLP 7543

BS 4790 Low Radius  
ASTM E648 Class 1  
ASTM E662 < 450  
ASTM D 2859 Passes

BS EN ISO 354 NRC 0,30 or higher


Certification




Specifications are subject to normal manufacturing tolerances, and subject to change without prior notice.  
As in all quality carpets, colors are subject to dye lot variations.

Installation Method

25 x 100 cm.



Random Vertical Brick



Herringbone



Visit the site

Sustainability  
Awards

Winner

Waste Elimination  
Carpets Inter EcoSoft® carpet tiles

