



Desert 9502



Specifications

Construction	Tufted Structured Loop	
Fibre	BCF Polyamide 6 & ECONYL®	
Dye Method	100% Solution Dyed	
Pattern Repeat	None	
Tufted Weight	17.4oz	
Gauge	1/10"	
Finished Pile Thickness	3.2mm	
Total Thickness	6.0mm	
Product Size	500mm x 500mm	
Primary Backing	Polyester Fleece	
Secondary Backing	Desso Ecobase® tile	
ISO 9239.1: 2010 Fire Test	Critical Radiant Flux ≥ 8.0kW/m²	
Electrostatic Propensity	Less than 2.0 kv	
Warranty	10 Years	
Environmental	Greentag Cradle to Cradle Silver Certified	
Recyclability	100% recyclable	
Materials	Does not contain PVC, Phthalates, or PBD/PBDE	
Recycled Content:	9094	9502
- Total Recycled Content by Weight	54.5%	60.9%
- Pre-consumer	50.5%	53.7%
- Post-consumer	4.0%	7.2%
Installation Options	<div><div><div>↔↔↔↔</div><div>↑↑↑↑</div><div>↑↓↑↓</div><div>→↑↓↑</div></div><div>Random</div><div><div>↑↑↑↑</div><div>↑↑↑↑</div><div>↑↑↑↑</div><div>↑↑↑↑</div></div><div>Quarter turn</div></div>	

