



**JACOBSEN
BRINGS YOU**

Medintone™

DIAMOND 10™ Coated
Homogeneous Sheet
ColourArt™

Suitable for all residential and
commercial applications such as:

- > Aged Care > Retail > Bathroom
- > Education > Kitchen > Rumpus
- > Healthcare > Living rooms > Bedroom
- > Workplace > Entrance

Disclaimer: The information given here is correct at the date of publication however, due to Armstrong Flooring's commitment to ongoing product improvement, Armstrong reserves the right to modify this information without prior notice. Please note that Armstrong Flooring's instructions regarding installation, cleaning and maintenance must be observed. Please refer to jacobsen.co.nz for guidance. The colour images provided are indicative only.

Specifications

Type of floor covering	ISO 10581	Homogeneous Sheet Vinyl
Coating	DIAMOND 10™	
Manufactured	China	
Overall Thickness	ISO 24346	2.0mm
Roll Dimensions	ISO 24341	2m x 18m
Product Weight	ISO 23997	2.65kg/m ²
Binder Content	ISO 10581	Type 1
Wear Resistance	EN 660-2	Group T
Residual Indentation	ISO 24343-1	≤ 0.10mm (PASS)
Dimensional Stability	ISO 23999	≤ 0.4%
Castor Chair	ISO 4918	Pass
Flexibility	ISO 24344 method A	Pass 20mm mandrel
Seam Strength	ISO 16906	≥ 240 (PASS)
Colour Fastness	ISO 105-B02	≥ 6 (PASS)
Resistance to Staining	ISO 26987	0 (No Stain)
Slip Resistance	AS 4586:2013	SRV: 28
Fire Resistance (Flooring)	ISO 9239-1 2010	
Critical Radiant Flux	> 11kW/m ² (PASS)	
Classification (Use Area)	ISO 10874	Industrial: 43 (Heavy) Commercial: 34 (Very Heavy)
Antistatic Resistance	EN1815 method A and EN14041	≤ 2kV (PASS)



Tough as Diamonds

- Unique formulation with diamond infused surface.
- Market leading scratch, stain and scuff resistance.



Easy to Maintain

- Outstanding dirt and stain-resistant qualities for easy cleaning and maintenance.
- Enhanced appearance retention.
- No burnishing required.



Exceptional Durability

- Industrial Rating (Class 43 – heavy).
- Commercial Rating (Class 34 – very heavy).
- Wear Resistance Classification (Group T).
- Type 1 Binder content (Pass).



Chemical Resistance

- Next generation chemical resistance.
- Minimises risk medicament and strong acid/alkali from damaging the flooring.

Jacobsen®


ArmstrongFlooring™

Talk to one of our experts, or visit our website:

0800 800 460 | customer.services@jacobsen.co.nz | jacobsen.co.nz



NZ Stock Colours



Almost Black



Brown Umbra




Cool White




Gray Light



Little Black Book



Natural Gray



Natural Gray Dark



Natural White



Rock Brown




Rock Dust Light


Special Order




All Fired Up



Blue Lagoon



Deep Gray




Flamingo




Gold Leaf




Golden Sun



Grayed Blue Light




Grayed Blue Mid




Grayed Blue




Hazel



Hydrangea



Indigo Mid



Indigo



Light Aubergine




Light Chocolate

Jacobsen® | ArmstrongFlooring™

Talk to one of our experts, or visit our website:
0800 800 460 | customer.services@jacobsen.co.nz | jacobsen.co.nz




Special Order



Lime Grass




Maize Yellow



Mazarine Blue




Milk Chocolate



Mosaic Blue




Natural Gray Light



Natural Tone




Natural



Ocean Blue




Orchid Mist



Perfectly Plum




Powder Chocolate




Promise Green



Refresh Green Mid




Regatta




Rock Dust Mid




Sand Light




Sand Mid



Soft Green Light



Tangerine



Walnut



Zaffron

Jacobsen® | ArmstrongFlooring™

Talk to one of our experts, or visit our website:
0800 800 460 | customer.services@jacobsen.co.nz | jacobsen.co.nz

