

Suitable for all residential applications such as:

- > Bedroom > Entrance
- > Living Room > Rumpus

Our goods come with guarantees that cannot be excluded under the New Zealand Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably forseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality. The colour images provided are indicative only, please refer to physical samples for final colour selection.

> Stairs

EForce 038 Ultra Primose 033 Coastal Description	E-Force 042 Flux Primose 093 Himalayan	E-Force 093 Wave Primose 096 Rock	E-Force 096 Volt Primose 097 Ruby Mountain
Product Name	E-Force		Primrose
Carpet Description	Cut Pile Hard	Twist	Cut Pile Soft Touch
Construction	Tufted		
Size	500 x 500 mm		
Pack	4m2		3m2

 Pile Content
 100% Solution Dyed Nylon

 Rating
 Residential Extra Heavy Duty + Stairs Commercial Medium Duty

Specifications

Pile Height	6.7 mm	8.5 mm	
Total Thickness	9.3 mm	11.5 mm	
Pile Weight	1,270 grams/m2	1,430 grams/m2	
Backing	Cushion Backed		
Fire Rating - CHF (EN ISO 9239.1:2010)	8.2kW/m2	8.9kW/m2	
Acoustic - Lw (EN ISO 10140)	28dB	31dB	
Colour Variation	Colour may vary from dye lot to dye lot		
Installation	Carpet Tiles must be installed in accordance with AS/NZA 2455.2		
Cleaning + Maintenance	Cleaning and maintenance should be done in accordance with AS/NZA 3733:1995		
Shading (watermarking/ permanent pile reversal)	Shading is an inherent characteristic of (predominantly) cut pile carpets and is not recognised as a manufacturing fault.		

Jacobsen[®]

Talk to one of our experts, or visit our website:0800 800 460 | customer.services@jacobsen.co.nz | jacobsen.co.nz