




























	Standard	Result
 <b>Size</b>		See separate table
 <b>Thickness</b>	ISO 24346	6.5 mm
 <b>Wear layer</b>	ISO 24340	0.5 mm
 <b>Locking system<sup>1</sup></b>		5G® Fold Down installation system
 <b>Surface treatment</b>		K-Guard+ PU coating
<b>Warranty<sup>2</sup></b>	Commercial Domestic	15 years wear Lifetime wear
 <b>Bevelled edge</b>		Micro
 <b>Standards</b>	EN 16511	Pass: Multilayer modular floorcovering panels
 <b>Classification</b>	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
 <b>Reaction to fire</b>	EN ISO 9239.1:2010	CRF: 10.9 kW/m <sup>2</sup> Smoke Value: 169.38% min.
 <b>Staining</b>	EN 438-2	Pass (grade 5)
 <b>Light fastness</b>	EN ISO 105-B02	Pass (≥ 6)
 <b>Abrasion resistance</b>	EN 13329 Annex E	Pass (4000 cycles)
 <b>Furniture chair leg</b>	EN 424	Pass (no visible damage)
 <b>Dimensional stability</b>	BS EN ISO 23999	Pass (≤ 0.25%)
 <b>Swelling</b>	ISO 24336	Pass (0.2%)
 <b>Acoustic impact noise reduction</b>	EN ISO 10140-1:2016 NCC F5.3(a) requirement of ≤ 62 dB under ISO 717.2:2013 G6.3.2 impact insulation class ≥ 55 IIC ASTM E492-09	ΔL <sub>w</sub> = 21 dB Ln,w = 52 dB Pass IIC 62 Suitable for use on upper floors of residential high rise apartment buildings without the need for a separate acoustic underlay
 <b>Indentation - residual</b>	ISO 24343-1	Pass (< 0.1 mm)
 <b>Impact resistance</b>	EN 13329 Annex F	Pass (≥ 1800 mm)
 <b>Castor chair continuous use</b>	EN 425/ISO 4918	Pass (25,000 cycles)
 <b>Thermal resistance</b>	ISO 8302	0.0515 m <sup>2</sup> K/W Suitable for underfloor heating. Max 27°C
 <b>Slip resistance<sup>3</sup></b>	AS4586:2013 Appendix D	R10
 <b>Adhesive</b>		None required; please install according to our installation instructions.
<b>Environmental</b>	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
 <b>Indoor Air Comfort</b>	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.
 <b>Environmental Product Declaration</b>	Environmental Product Declaration	Product-specific Type III EPD (products with external third-party verification)
 <b>NSF/ANSI 332</b>	NSF/ANSI 332	Sustainability Assessment for Resilient Floor Coverings; Silver certified product
 <b>Recycling</b>		Suitable
 <b>Phthalate free</b>		Yes

<sup>1</sup> 5G® is a patented technology invented by Välinge Innovation AB. The 5G® word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

<sup>2</sup> Subject to terms. Please see our website.

<sup>3</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

**Australia**

Call: 1800 33 11 70

Email: [customerservice@karndean.com.au](mailto:customerservice@karndean.com.au)

Visit: [www.karndean.com](http://www.karndean.com)

**New Zealand**

Call: 0800 44 21 01

Email: [customerservice@karndean.co.nz](mailto:customerservice@karndean.co.nz)

Visit: [www.karndean.com](http://www.karndean.com)

Mar 22



Product Code	Size		Box Quantity		Slip Resistance Oil-Wet Ramp
	mm	inches	m <sup>2</sup>	Pieces	
RKP8101	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8103	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8104	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8105	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8106	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8108	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8112	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8116	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8118	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8119	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8120	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8121	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8201	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8203	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8205	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8207	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8208	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8210	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8213	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKP8216	1420.0 x 225.0	55.91" x 8.86"	3.195	10 Planks	R10
RKT2409	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT2410	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT2411	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT2412	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT2413	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT2414	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT2415	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT3006-G	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT3014-G	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT3015-G	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT3016-G	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10
RKT3017-G	457.0 x 600.0	17.99 x 23.62	2.742	10 Tiles	R10