




Specifications

Construction	Pattern Loop
Fibre	Eco Solution Q™ Nylon
Dye Method	100% Solution Dyed
Pattern Repeat	None
Tufted Weight	16oz/yd ²
Gauge	1/12"
Finished Pile Thickness	3.96mm
Total Thickness	5.3mm
Product Size	610mm x 610mm
Primary Backing	Synthetic
Secondary Backing	Ecoworx™
Protective Treatments	SSP® Shaw Soil Protection
ISO 9239.1: 2010 Fire Test	Mean Critical Radiant Flux 7.7kW/m ²
Electrostatic Propensity	Less than 3.5 kv
Warranty	Lifetime Commercial Limited
Environmental	Cradle to Cradle Silver Certified Declare Label - LBC Compliant
Recyclability	100% recyclable
Materials	Does not contain PVC, Phthalates, or PBD/PBDE
Recycled Content:	
- Total Recycled Content by Weight	44.4%
- Pre-consumer	33.3%
- Post-consumer	11.1%
Installation Options	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>quarter turn</p> </div> <div style="text-align: center;">  <p>monolithic</p> </div> </div>



Taharuu Bedrock



Taharuu Clay

