

Sekisui Pilon Pty Ltd

1 Parraweena Road, Taren Point, N.S.W. 2229 Australia
PO Box 2898, Taren Point, N.S.W. 2229 Australia
Telephone: 02 9525 9880 Facsimile: 02 9525 8004

TECHNICAL INFORMATION

Silent Shield Underlay

Product:

Physically cross linked, closed cell, grey polymeric foam, heat laminated to a silver polymeric film (Damping proofing membrane)

Roll Size:

Roll Width is 1000mm, plus an additional 100mm film overlap. Roll Length is 50m.

Acoustic:

Floor	FIIC	L'n,w+C
8mm high Pressure Laminate / 2mm Silent Shield		
underlay with film backing	57	47
7mm high Pressure Laminate / 2mm Silent Shield		
underlay with film backing	59	49
7mm Plywood based timber floating floor / 2mm		
Silent Shield underlay with film backing	56	49
14 mm timber floating floor / 2mm Silent Shield		
underlay with film backing	57	49

Comments:

- 1. A lower L'n,w+C represents a greater acoustic separation (The 2004 BCA Criteria for separation of hard floors is L'n,w+C of 62 or lower)
- 2. A higher FIIC represents a better impact isolation performance of the floor system.

Key functions of Silent Shield underlay:

- 1. Good impact sound insulator.
- 2. Excellent water vapour barrier.
- 3. Absorbs unevenness in the sub floor.
- 4. Lays flat for easy installation.
- 5. Resists mildew and fungi.
- 6. Combines all in one plastic sheeting plus underlay.

Installation Instructions:

- 1. Floor must be clean, smooth, level, and dry.
- 2. Unroll underlay plastic film facing concrete.
- 3. Lay with underlay edges butting to each other with film lap underneath.
- 4. Fold underlay 50mm up the wall surrounds.
- 5. Cover all joints with duct tape.



This information on Sekisui Pilon foams is presented to the best of our knowledge. All product data is based on average values and is for guidance only.

Recommendations as to methods of post fabrication, application and use of Sekisui Pilon foams are based on our experience and knowledge of the characteristics of our products and are given in good faith. As producer of the material we have no control over the application of Sekisui Pilon foams and no legal responsibility is accepted for such recommendations. In particular, no responsibility is accepted by us for any system in which Sekisui Pilon foams are utilised nor for any application. Softlon - Registered trademark of Sekisui Pilon