COMPACT **HOMOGENEOUS VINYL FLOORINGS**

PLUS ranges

Contract Plus Standard Plus Somplan Plus

Cleaning instructions

Modern day-room cleaning aims to reduce wet cleaning procedures and replace them with drier cleaning techniques. For example, the use of centrally laundered pre-impregnated mops and the wide application of appropriate machines. This makes work more effective and easier for the cleaning staff, and minimises environmental impact. Less cleaning chemicals and less fresh water are used.

Jan 2011

General advice

- Clean the floorcovering regularly, as this is more cost-effective and hygienic than occasional heavy-duty cleaning.
- Always follow dosage instructions carefully.
- Wipe up any grease and spilt oil immediately, as they may damage the surface.
- Resilient floors are damaged by solvents.
- Black rubber wheels and rubber feet can discolour the floorcovering. All chair and table legs should have good quality floor protectors. Felt pads are not recommended in commercial interiors. Hard plastic is preferred.
- Remember that light colours need more frequent cleaning.





Entrance matting

About 80% of surface soiling that has to be cleaned off is brought in from outside. And 90% of that soiling can be avoided using an effective and correctly dimensioned entrance mat. The less dirt that comes in through the entrance, the lower the maintenance requirements.

Daily and regular cleaning





Dry mopping

Remove dust and dirt with yarn or microfibre mops, or disposable mops, dry or impregnated. You can also use a suitable broom with soft bristles.



Damp mopping

Use a mop dampened with water or detergent solution. It is essential that water does not stay on the floor or leave a film. The floor should be virtually dry after 15-20 seconds.



Machine cleaning

For best results, clean the floor gently with a combined scrubber/dryer machine and medium hard brushes or preferably red pads.

Cleaning chemicals: If wet cleaning is necessary, use a neutral floor cleaner. Wet-rooms may necessitate occasional cleaning with acidic cleaning agents, pH 3 to 5, in order to remove residual lime and soap.



Spot and stain removal

Treat stains immediately.

Spot clean by hand with a white/red nylon pad and neutral detergent (solvents should not be used). Work from the outside of the mark towards its centre. Rinse and wipe afterwards with clean water.

Periodic cleaning





Spray polishing / Spray cleaning

To restore worn areas, traffic lanes and scuff marks.

Polish systems can be used depending on requirements and prevailing conditions. It is essential to follow the chemical manufacturer's instructions carefully for the treatment system.

FOR HEAVY WEAR AND SOILING







Machine scrubbing + Wet vacuuming

Apply the cleaning solution (a fairly strong cleaning agent, pH 10-11, added to water) to the flooring and allow to penetrate for 5-10 minutes. Clean the floor using a heavy single scrub machine and red cleaning pad. Vacuum away the dirty water immediately. Rinse with clear water, Allow the floor to dry.

If you have any questions, please contact your local Tarkett representative for further information. The above information is subject to change due to continuous improvement.



For low-maintenance properties

The Plus range offers products with <a good quality at an attractive price. These vinyl floorcoverings are surface-treated with PUR, for low-maintenance properties. This improved cleanability offers maintenance cost savings when compared with non-treated materials.

Initial site clean

with thick paper or

Always protect the floor

hardboard sheeting during the construction period. After installation, we recommend an initial site clean: vacuum, sweep or damp mop the area to remove building dust and loose dirt. A combined scrubber/dryer with brushes or white/yellow pads cleans large areas very effectively. Use detergent with a low pH (3-5).

