# Technical Data Sheet Product: **DT022**



## **DESCRIPTION**

This andodised aluminium profile is designed for a neat transition between 5mm vinyl and carpet. This eliminates the need and expense of matrixing the floor to raise the vinyl to the carpet height.

### **MATERIAL**


T6 6063 Alloy aluminium - Natural Satin anodised.

Standard 2.5 Meter Lengths.

Supplied pre drilled for countersunk screw fixing.

### **DIMENSIONS**

#### **EXAMPLE**



In this installation, DTO22 in natural satin has been used to create a hazard free transition between 5mm LVT and carpet tile. the edge of the strip covers the edge of the carpet sightly.



For PDF and CAD drawings with full dimensions and installation guides, please refer to our website <a href="https://www.tredsafe.co.nz">www.tredsafe.co.nz</a>

Release: January 2019

Information given in this data sheet is based on the current state of knowledge. This does not exempt the purchaser from carrying out his own careful inspections of incoming goods and their suitability for local building codes. We reserve the right to make changes to the product data in the course of technical progress or due to operationally related further development. Owing to factors beyond our control during application, recommendations given in this data sheet require tests and experiments by the customer. Our recommendations do not exempt the customer from the obligation to check any infringements of third-party rights himself and eliminate them if necessary. The suggestions for product use are not equivalent to a warranty of its suitability for the recommended purpose.

Each new release of this data sheet supersedes the previous one.