Technical Data Sheet Product: **DT026**





DESCRIPTION

This profile is an expansion gap joint system designed for carpeted floors. Designed for use with direct stick carpets or carpet tiles and suitable for interior or exterior uses. Carpet can be installed in the recess space and supplied in 2.5 meter lengths.


MATERIAL

T6 6063 Alloy aluminium - Natural Satin anodised.

Standard 2.5 Meter Lengths.

Supplied pre drilled on one side of recess.

EXAMPLE



For this installation, DT026 has been laid between 2mm carpet tile. Matching carpet has been used in this installation for a smooth and tidy transition.



For PDF and CAD drawings with full dimensions and installation guides, please refer to our website <u>www.tredsafe.co.nz</u>

Release: January 2019

Information given in this data sheet is based on the current state of knowledge. This does not exempt the purchaser from carrying out his own careful inspections of incoming goods and their suitability for local building codes. We reserve the right to make changes to the product data in the course of technical progress or due to operationally related further development. Owing to factors beyond our control during application, recommendations given in this data sheet require tests and experiments by the customer. Our recommendations do not exempt the customer from the obligation to check any infringements of third-party rights himself and eliminate them if necessary. The suggestions for product use are not equivalent to a warranty of its suitability for the recommended purpose.

Each new release of this data sheet supersedes the previous one.