# Technical Data Sheet Product: **DT056**





## DESCRIPTION

Designed to cover floor / wall transition the semi-rigid flexi-PVC profile can be installed on flat or curved wall surfaces. The profile has a self-stick backing tape that will adhere to smooth wall surfaces with the curved base of the profile covers any expansion or tolerance gaps from selected flooring used


### MATERIAL

Semi-rigid PVC. Available in white only. (Surface is Paintable)

Standard 20 Metre rolls. (Boxed)

#### DIMENSIONS

EXAMPLE



In this example DT056 has created a smooth transition between the flooring LVT and wall. The profile replaces the need for a skirting board.



For PDF and CAD drawings with full dimensions and installation guides, please refer to our website <u>www.tredsafe.co.nz</u>

#### Release: January 2019

Information given in this data sheet is based on the current state of knowledge. This does not exempt the purchaser from carrying out his own careful inspections of incoming goods and their suitability for local building codes. We reserve the right to make changes to the product data in the course of technical progress or due to operationally related further development. Owing to factors beyond our control during application, recommendations given in this data sheet require tests and experiments by the customer. Our recommendations do not exempt the customer from the obligation to check any infringements of third-party rights himself and eliminate them if necessary. The suggestions for product use are not equivalent to a warranty of its suitability for the recommended purpose.

Each new release of this data sheet supersedes the previous one.