Technical Data Sheet Product: **DT070**



DESCRIPTION

Multi-purpose joint system designed for floating floors requiring expansion gaps. This robust rotating design is designed for 0mm - 15mm height variations. This anodised aluminium profile is available in natural satin or champagne finish.

MATERIAL


T6 6063 Alloy aluminium - Available in Natural Satin and Champagne.

Standard 2.5 Metre Lengths.


Supplied pre drilled for countersunk screw fixing (screws supplied).

DIMENSIONS

EXAMPLE



In this installation, DT070 has been used to provide a construction joint between 2mm vinyl and 15mm LVT. The profile creates a tidy finish and removes the trip hazard.



For PDF and CAD drawings with full dimensions and installation guides, please refer to our website www.tredsafe.co.nz

Release: January 2019

Information given in this data sheet is based on the current state of knowledge. This does not exempt the purchaser from carrying out his own careful inspections of incoming goods and their suitability for local building codes. We reserve the right to make changes to the product data in the course of technical progress or due to operationally related further development. Owing to factors beyond our control during application, recommendations given in this data sheet require tests and experiments by the customer. Our recommendations do not exempt the customer from the obligation to check any infringements of third-party rights himself and eliminate them if necessary. The suggestions for product use are not equivalent to a warranty of its suitability for the recommended purpose.

Each new release of this data sheet supersedes the previous one.