

Granit Safe.T

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 13845	Polyvinyl chloride floor coverings with particle based enhanced slip resistance
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	42 General
Technical Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2 mm
Total weight	ISO 23997	2950 g/m ²
Surface treatment		Safety Clean XP
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #		0019-0006-DoP-2013-07
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 11.0kW/m ² Smoke 88%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	ISO 10456	0,010 m ² ·K/W
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,10 mm Best measured value: 0,02 mm
Dimensional stability	EN ISO 23999	Average Measured Value : ≤ 0.40 %
Slip resistance	DIN 51130	R11
	DIN 51097	Class B
	AS 4586 96 Slider** 55 Slider**	P4 P5
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Castor chair	ISO 4918	Suitable
Colour fastness to light	ISO 105-B02	≥ 7
Underfloor heating	BS 8203	Suitable (subfloor temperature maximum 27°C)
Curl resultant to heat	EN ISO 23999	≤ 8 mm
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		6,79 kg CO ₂ eq /m ²
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m ³)
GreenTag		Level A
HealthRATE		Platinum
Dimensions and designs		
Roll		Roll 2 x 25 m
Number of designs available		24

** When comparing P values for slip ratings a 96 slider replicates footwear, a 55 slider replicates barefoot. The 55 slider results should be used for barefoot applications such as showers.



The above information is subject to modification for the benefit of further improvement (27/1/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.