

Safetred Universal Plus R12

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 13845	Polyvinyl chloride floor coverings with particle based enhanced slip resistance
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2.10 mm
Total weight	ISO 23997	3350 g/m ²
Surface treatment		TEKTANIUM™
Binder content	ISO 10582	Type I
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance		0170-0018-DoP-2020-10
UKCA - DoC certificate		0170-0018-DoC-202205
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 8.9kW/m ² Smoke 113%.min
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Electrical resistance	EN 1081	Static dissipative (≤ 1x10 ⁹ Ω)
Thermal resistance (m ² K/W)	ISO 10456	0,020 m ² ·K/W
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Abrasion particle loss	EN 13845 Annex D	≤ 10%
Dimensional stability	EN ISO 23999	≤ 0.10 %
Slip resistance	DIN 51130 AS 4586	R12 P5
Slip Classification	EN 13845 Annex C	ESf
Surface Roughness Rz	BS 7679-2	≥ 35µm
Furniture leg effect	ISO 16581	No damage
Castor chair effect	ISO 4918	No damage
Colour fastness to light	ISO 105-B02	≥ 7
Impact sound reduction - ΔLw	EN ISO 717-2	4 dB
Underfloor heating	BS 8203	Suitable (maximum 27°C)
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Chemical resistance	ISO 26987	Good resistance
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Vinyl Council Australia		PVC Best Practice
Recyclability through Resilooop		Recyclable
Total recycled content		42 %
TVOC emissions after 28 days	EN 16516	Platinum (≤ 10 µg/m ³)
Dimensions and designs		
Roll		Roll 2x20m
Number of designs available		4



The above information is subject to modification for the benefit of further improvement (01/06/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett Australia
 Suite 1, Level 3, 3 Columbia Court, Baulkham Hills NSW 2153
 (02) 8853 1200
customerservice@tarkett.com
www.tarkett.com.au

